SIEMENS

Data sheet

6GK1901-1BB11-2AA0

product type designation product description

IE FC RJ45 Plug 180 (4x2)

RJ45 data connector

FastConnect system

Industrial Ethernet FastConnect RJ45 plug 180 4x 2, RJ45 plug-in connector (10/100/1000 Mbit/s) with rugged metal enclosure and FC connection system, for IE FC TP cable 4x 2 (AWG24); 180° cable outlet 1 pack = 1 unit.

For connection to IE FC TP cables 4x2, suitable for fast assembly with the



suitability for use

transfer rate transfer rate / for Industrial Ethernet 10 Mbit/s, 100 Mbit/s, 1000 Mbit/s interfaces number of electrical connections • for Industrial Ethernet FC TP cables 1 • for network components or terminal equipment 1 type of electrical connection • for Industrial Ethernet FC TP cables integrated cut-and-clamp contacts for 8-wire TP FC installation cable · for network components or terminal equipment RJ45 connector type of electrical connection / FastConnect Yes mechanical data material / of the enclosure metal number of reuses 10 locking mechanism design other design, dimensions and weights type of cable outlet 180° cable outlet width 13.7 mm height 16 mm 55 mm depth 35 g net weight 6.5 ... 8 mm connectable cable cross-section 0.21 ... 0.33 mm² connectable conductor cross-section ambient temperature during operation -40 ... +85 °C • during storage -40 ... +85 °C -40 ... +85 °C during transport relative humidity • at 25 °C / without condensation / during operation / 95 % maximum protection class IP IP20 product features, product functions, product components / general product feature PoE capability Yes PoE+capability Yes • silicon-free Yes

product component	_			
product component strain relief 		Yes		
standards, specifications, approvals	- 11	165		
	- 1			
certificate of suitability		Yes		
RoHS conformity				
• UL approval		Yes		
• cULus approval		Yes		
railway application in accordance with EN 50155	_	No		
standard for structured cabling	(Cat6		
reference code				
according to IEC 81346-2:2019		XGA		
further information / internet links				
internet link				
 to website: Selection guide for cables and connectors 		https://support.industry.siemens.com/cs/ww/en/view/109766358		
 to web page: selection aid TIA Selection Tool 		https://www.siemens.com/tstcloud		
• to website: Industrial communication		https://www.siemens.com/simatic-net		
• to web page: SiePortal		https://sieportal.siemens.com		
• to website: Image database		https://www.automation.siemens.com/bilddb		
• to website: CAx-Download-Manager		http://www.siemens.com/cax		
• to website: Industry Online Support		https://support.industry.siemens.com		
security information				
		for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)		
Approvals / Certificates				
General Product Approval				Test Certificates
Declaration of Con- formity][<u>Miscellaneous</u>	<u>Special Test Certific-</u> <u>ate</u>
Marine / Shipping		Environment	Industrial Communic	ation
DIVU LIS RIT		<u>Confirmation</u>	PROFINET	
last modified:		11/8/2024 🕑		