



Figure similar

SIMATIC DP, ET 200ECO PN, 8 DIO 24 V DC/1.3 A; 8xM12, Degree of protection IP67

General information	
Vendor identification (VendorID)	002AH
Device identifier (DeviceID)	0306H
Supply voltage	
Rated value (DC)	24 V
Reverse polarity protection	Yes
power supply according to NEC Class 2 required	Yes
Load voltage 2L+	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption, typ.	100 mA
from supply voltage 1L+, max.	4 A
from load voltage 1L+ (unswitched voltage)	4 A
from load voltage 2L+, max.	4 A
Encoder supply	
24 V encoder supply	
Short-circuit protection	Yes; Electronic
Output current, max.	100 mA; per output
Power loss	
Power loss, typ.	6.5 W
Digital inputs	
Number of digital inputs	8
in groups of	4
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Number of simultaneously controllable inputs	
all mounting positions	
— up to 60 °C, max.	8
Input voltage	
Rated value (DC)	24 V
for signal "0"	-3 to +5V
for signal "1"	+11 to +30V
Input current	
for signal "1", typ.	7 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", max.	typically 3 ms

— at "1" to "0", max.	typically 3 ms
Cable length	
• unshielded, max.	30 m
Digital outputs	
Number of digital outputs	8
• in groups of	4
Short-circuit protection	Yes; Electronic
• Response threshold, typ.	1.8 A
Limitation of inductive shutdown voltage to	Typ. (L1+, L2+) -47 V
Controlling a digital input	Yes
Switching capacity of the outputs	
• on lamp load, max.	5 W
Output current	
• for signal "1" rated value	1.3 A; Maximum
• for signal "1" permissible range, max.	1.3 A
• for signal "0" residual current, max.	1.5 mA
Parallel switching of two outputs	
• for uprating	No
• for redundant control of a load	Yes
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	0.5 Hz
• on lamp load, max.	1 Hz
Total current of the outputs (per group)	
all mounting positions	
— up to 60 °C, max.	3.9 A
Cable length	
• unshielded, max.	30 m
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
Interfaces	
Transmission procedure	100BASE-TX
Number of PROFINET interfaces	1
1. Interface	
Interface types	
• M12 port	Yes
• integrated switch	Yes
Interface types	
M12 port	
• Autonegotiation	Yes
• Autocrossing	Yes
• Transmission rate, max.	100 Mbit/s
Protocols	
Supports protocol for PROFINET IO	Yes
PROFINET CBA	No
PROFIsafe	No
PROFINET IO Device	
Services	
— IRT with the option "high flexibility"	Yes
— Prioritized startup	Yes
Redundancy mode	
Media redundancy	
— MRP	Yes
Open IE communication	
• TCP/IP	No
• SNMP	Yes
• DCP	Yes
• LLDP	Yes

- ping - ARP	Yes		
Interrupts/diagnostics/status information			
Diagnostics function	Yes		
Alarms			
Diagnostic alarm	Yes		
Diagnoses			
- Diagnostic information readable - Monitoring the supply voltage - Wire-break in actuator cable - Wire-break in signal transmitter cable - Short-circuit - Short-circuit encoder supply - Group error	Yes Yes; green "ON" LED Yes Yes Yes Yes Yes; Red/yellow "SF/MT" LED		
Potential separation			
between the load voltages	Yes		
between load voltage and all other switching components	No		
between Ethernet and electronics	Yes		
Potential separation channels			
between the channels	No		
Isolation			
tested with			
24 V DC circuits - Test voltage for interface, rms value [Vrms]	707 V DC (type test) 1 500 V; According to IEEE 802.3		
Degree and class of protection			
IP degree of protection	IP65/67		
Standards, approvals, certificates			
Suitable for safety-related tripping of standard modules	No		
Use in hazardous areas			
- Explosion protection category for gas - Explosion protection category for dust	ATEX II 3G Ex nA II T4 ATEX II 3D Ex tc IIIC T90°C Dc		
connection method			
Design of electrical connection	4/5-pin M12 circular connectors		
Dimensions			
Width	60 mm		
Height	175 mm		
Depth	49 mm		
Weights			
Weight, approx.	910 g		
Classifications			
		Version	Classification
	eClass	14	27-24-26-04
	eClass	12	27-24-26-04
	eClass	9.1	27-24-26-04
	eClass	9	27-24-26-04
	eClass	8	27-24-26-04
	eClass	7.1	27-24-26-04
	eClass	6	27-24-26-04
	ETIM	9	EC001599
	ETIM	8	EC001599
	ETIM	7	EC001599
	IDEA	4	3566
	UNSPSC	15	32-15-17-05
Approvals / Certificates			
General Product Approval			



[Miscellaneous](#)



[Manufacturer Declaration](#)



[KC](#)

General Product Approval	EMV	For use in hazardous locations			
--------------------------	-----	--------------------------------	--	--	--



[CCC-Ex](#)



For use in hazardous locations	Marine / Shipping				
--------------------------------	-------------------	--	--	--	--

[Miscellaneous](#)



[NK / Nippon Kaiji Kyokai](#)

Marine / Shipping		Industrial Communication			
-------------------	--	--------------------------	--	--	--



[CCS \(China Classification Society\)](#)



[PROFINET](#)

last modified: 4/7/2025 