

## Data sheet

**6GK7343-1CX10-0XE0**

product type designation



## CP 343-1 Lean

Communications processor CP 343-1 Lean for connection of SIMATIC S7-300 to Industrial Ethernet via TCP/IP and UDP, Multicast, SEND/RECEIVE with and without RFC1006, Fetch/ Write, S7 communication (server), PROFINET IO device integrated 2-port switch ERTEC 200, Module replacement without PG, SNMP diagnostics, initialization via LAN, 2x RJ45 connection for LAN with 10/100 Mbit/s

transfer rate	
transfer rate <ul style="list-style-type: none"><li>at the 1st interface</li></ul>	10 ... 100 Mbit/s
interfaces	
number of interfaces / according to Industrial Ethernet	2
number of electrical connections <ul style="list-style-type: none"><li>at the 1st interface / according to Industrial Ethernet</li><li>for power supply</li></ul>	2 1
type of electrical connection <ul style="list-style-type: none"><li>of Industrial Ethernet interface</li><li>at the 1st interface / according to Industrial Ethernet</li></ul>	RJ45 port RJ45 port
type of electrical connection <ul style="list-style-type: none"><li>for power supply</li></ul>	2-pole plugable terminal block
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	5 V
supply voltage	24 V
supply voltage / external	24 V
supply voltage / external / at DC / rated value	24 V
relative positive tolerance / at DC / at 24 V	20 %
relative negative tolerance / at DC / at 24 V	15 %
consumed current <ul style="list-style-type: none"><li>from backplane bus / at DC / at 5 V / typical</li><li>from external supply voltage / at DC / at 24 V / typical</li><li>from external supply voltage / at DC / at 24 V / maximum</li></ul>	0.2 A 0.16 A 0.2 A
power loss [W]	5.8 W
ambient conditions	
ambient temperature <ul style="list-style-type: none"><li>for vertical installation / during operation</li><li>for horizontally arranged busbars / during operation</li><li>during storage</li><li>during transport</li></ul>	0 ... 40 °C 0 ... 60 °C -40 ... +70 °C -40 ... +70 °C
relative humidity <ul style="list-style-type: none"><li>at 25 °C / without condensation / during operation / maximum</li></ul>	95 %
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-300 single width
width	40 mm

height	125 mm
depth	120 mm
net weight	0.22 kg
fastening method	
• S7-300 rail mounting	Yes
<b>performance data / open communication</b>	
number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	8
data volume	
• as user data per ISO on TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum	8 Kibyte
• as user data per TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum	8 Kibyte
• as user data per UDP connection / for open IE communication / by means of SEND/RECEIVE blocks / maximum	2 Kibyte
number of Multicast stations	8
<b>performance data / S7 communication</b>	
number of possible connections / for S7 communication	
• maximum	4
service	
• of SIMATIC communication / as server	Yes
<b>performance data / multi-protocol mode</b>	
number of active connections / with multi-protocol mode	12
<b>performance data / PROFINET communication / as PN IO controller</b>	
product function / PROFINET IO controller	No
<b>performance data / PROFINET communication / as PN IO device</b>	
product function / PROFINET IO device	Yes
data volume	
• as user data for input variables / as PROFINET IO device / maximum	512 byte
• as user data for output variables / as PROFINET IO device / maximum	512 byte
• as user data for input variables / for each sub-module as PROFINET IO device	240 byte
• as user data for output variables / for each sub-module as PROFINET IO device	240 byte
• as user data for the consistency area for each sub-module	240 byte
number of submodules / per PROFINET IO-Device	32
<b>performance data / telecontrol</b>	
protocol / is supported	
• TCP/IP	Yes
<b>product functions / management, configuration, engineering</b>	
product function / MIB support	Yes
protocol / is supported	
• SNMP v1	Yes
• DCP	Yes
• LLDP	Yes
configuration software	
• required	STEP 7 V5.4 or higher / STEP 7 Professional V11 (TIA Portal) or higher
identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 - higher level designation/location designation	Yes
product function / is supported / identification link	Yes
<b>product functions / diagnostics</b>	
product function / web-based diagnostics	Yes
<b>product functions / switch</b>	
product feature / switch	Yes
product function	
• switch-managed	No
• with IRT / PROFINET IO switch	No

• configuration with STEP 7	Yes
<b>product functions / redundancy</b>	
product function	
• ring redundancy	Yes
• redundancy manager	No
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
<b>product functions / security</b>	
product function	
• password protection for Web applications	No
• ACL - IP-based	Yes
• ACL - IP-based for PLC/routing	No
• switch-off of non-required services	Yes
• blocking of communication via physical ports	Yes
• log file for unauthorized access	No
<b>product functions / time</b>	
product function / SICLOCK support	Yes
product function / pass on time synchronization	Yes
protocol / is supported	
• NTP	Yes
<b>standards, specifications, approvals</b>	
reference code	
• according to IEC 81346-2:2019	KEC
<b>further information / internet links</b>	
internet link	
• to web page: selection aid TIA Selection Tool	<a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a>
• to website: Industrial communication	<a href="https://www.siemens.com/simatic-net">https://www.siemens.com/simatic-net</a>
• to web page: SiePortal	<a href="https://sieportal.siemens.com/">https://sieportal.siemens.com/</a>
• to website: Image database	<a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a>
• to website: CAX-Download-Manager	<a href="https://siemens.com/cax">https://siemens.com/cax</a>
• to website: Industry Online Support	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>security information</b>	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit <a href="https://www.siemens.com/cybersecurity-industry">www.siemens.com/cybersecurity-industry</a> . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <a href="https://www.siemens.com/cert">https://www.siemens.com/cert</a> . (V4.7)

#### Approvals / Certificates

##### General Product Approval



EG-Konf.

[Declaration of Con-  
formity](#)



CCC



UL

General Product Ap-  
proval

EMV

For use in hazardous locations



RCM

[KC](#)






ATEX



IECEx

[FM](#)

[CCC-Ex](#)

For use in hazard-ous locations	Marine / Shipping	other	Environment
		<a href="#">Confirmation</a>	<a href="#">Confirmation</a>
			

last modified: 12/8/2024 