

product type designation

product description

IE FC M12 Plug PRO (PROFINET)

M12 connector with high protection, 4-pole, D-coded

Industrial Ethernet FastConnect M12 plug PRO 2x2 M12 plug-in connector with rugged metal enclosure and FC connection method, with axial cable outlet (D-coded) 1 pack=1 unit for SCALANCE X208 PRO and ET 200 PRO PN.



suitability for use

For connecting electrical cables to SCALANCE X208PRO, ET200 PRO PN or ET200 eco PN for fast assembly with the FastConnect system

transfer rate

transfer rate / for Industrial Ethernet

10 Mbit/s, 100 Mbit/s

interfaces

number of electrical connections

- for Industrial Ethernet FC TP cables
- for network components or terminal equipment

4

1

type of electrical connection

- for Industrial Ethernet FC TP cables

integrated cut-and-clamp contacts for 4-wire TP FC installation cable AWG22

type of electrical connection / FastConnect

Yes

mechanical data

material / of the enclosure

metal

number of reuses

10

locking mechanism design

Screwed joint

tightening torque / for M12 round connector / maximum

0.6 N·m

connector coding / of the M12 circular connector

D

design, dimensions and weights

type of cable outlet

180° cable outlet

width

19 mm

height

19 mm

depth

73 mm

net weight

40 g

connectable cable cross-section

6.5 ... 6.5 mm

connectable conductor cross-section

0.33 mm²

ambient conditions

ambient temperature

- during operation
- during storage
- during transport

-40 ... +85 °C

-40 ... +85 °C

-40 ... +85 °C

relative humidity

- at 25 °C / without condensation / during operation / maximum

95 %

chemical resistance

- to water







resistant

protection class IP

IP65/67

product features, product functions, product components / general

product feature

<ul style="list-style-type: none"> • PoE capability • PoE+capability • silicon-free 	Yes Yes Yes								
product component									
<ul style="list-style-type: none"> • strain relief 	Yes								
standards, specifications, approvals									
certificate of suitability									
<ul style="list-style-type: none"> • RoHS conformity • UL approval • cULus approval • railway application in accordance with EN 50155 	Yes Yes Yes No								
standard for structured cabling	Cat5								
reference code									
<ul style="list-style-type: none"> • according to IEC 81346-2:2019 	XGA								
standards, specifications, approvals / Environmental Product Declaration									
Environmental Product Declaration	Yes								
global warming potential [CO2 eq]									
<ul style="list-style-type: none"> • total • during manufacturing • during operation • after end of life 	0.32 kg 0.28 kg 0.01 kg 0.03 kg								
further information / internet links									
internet link									
<ul style="list-style-type: none"> • to website: Selection guide for cables and connectors • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to web page: SiePortal • to website: Image database • to website: CAX-Download-Manager • to website: Industry Online Support 	https://support.industry.siemens.com/cs/ww/en/view/109766358 https://www.siemens.com/tstcloud https://www.siemens.com/simatic-net https://sieportal.siemens.com https://www.automation.siemens.com/bilddb https://www.siemens.com/cax https://support.industry.siemens.com								
security information									
security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)</p>								
Approvals / Certificates									
<table> <tr> <th>General Product Approval</th><th>Marine / Shipping</th></tr> <tr> <td> Declaration of Conformity  CCC </td><td>  UL </td></tr> <tr> <td>  DNV </td><td>  LRS </td></tr> <tr> <td></td><td>  RINA </td></tr> </table>		General Product Approval	Marine / Shipping	Declaration of Conformity  CCC	 UL	 DNV	 LRS		 RINA
General Product Approval	Marine / Shipping								
Declaration of Conformity  CCC	 UL								
 DNV	 LRS								
	 RINA								
<table> <tr> <th>Environment</th><th>Industrial Communication</th></tr> <tr> <td>Confirmation</td><td>PROFINET</td></tr> </table>		Environment	Industrial Communication	Confirmation	PROFINET				
Environment	Industrial Communication								
Confirmation	PROFINET								

