6GK5208-0BA00-2AB2

Data sheet



SCALANCE XB208 managed Layer 2 IE switch 8x 10/100 Mbit/s RJ45 ports 1x console port; diagnostics LED redundant power supply IEC 62443-4-2 certified; temperature range 0 °C to +60 °C; DIN-rail mounting; default PROFINET.

product type designation		
product brand name	SCALANCE	
product type designation	XB208	
transfer rate		
transfer rate	10 Mbit/s, 100 Mbit/s	
interfaces / for communication / integrated	•	
number of electrical connections		
 for network components or terminal equipment 	8; RJ45	
interfaces / other		
number of electrical connections		
for operator console	1	
• for power supply	1	
type of electrical connection		
• for operator console	RJ11	
for management purposes	RJ45	
supply voltage, current consumption, power loss		
product component / connection for redundant voltage supply	Yes	
type of voltage / 1 / of the supply voltage	DC	
 supply voltage / 1 / rated value 	24 V	
supply voltage / 1 / rated value	19.2 28.8 V	
consumed current / 1 / maximum	0.17 A	
 type of electrical connection / 1 / for power supply 	6-pole terminal block	
 product component / 1 / fusing at power supply input 	Yes	
ambient conditions		
ambient temperature		
 during operation 	0 60 °C	
during storage	-40 +70 °C	
during transport	-40 +70 °C	
relative humidity		
 at 25 °C / without condensation / during operation / maximum 	95 %	
protection class IP	IP20	
design, dimensions and weights		
design	compact	
width	40 mm	
height	117 mm	
depth	109 mm	
net weight	0.25 kg	
material / of the enclosure	Polycarbonate (PC-GF10)	
fastening method		

 35 mm top hat DIN rail mounting 	Yes
product features, product functions, product components / gene	- 11
cascading in the case of a redundant ring / at reconfiguration	50
time of <\~0.3\~s	
cascading in cases of star topology	any (depending only on signal propagation time)
product functions / management, configuration, engineering	
product function	
• CLI	Yes
web-based management	Yes
 MIB support 	Yes
TRAPs via email	Yes
configuration with STEP 7	Yes
• RMON	Yes
 port mirroring 	Yes
 multiport mirroring 	Yes
• CoS	Yes
 PROFINET IO diagnosis 	Yes
switch-managed	Yes
PROFINET conformity class	В
network load class / according to PROFINET	3
telegram length / for Ethernet / maximum	1632 byte
protocol / is supported	
• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• SFTP	Yes
• DCP	Yes
• LLDP	Yes
EtherNet/IP	Yes
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
IGMP (snooping/querier)	Yes
identification & maintenance function	
1&M0 - device-specific information	Yes
I&M1 - higher level designation/location designation	Yes
product functions / diagnostics	
product functions / diagnostics	
•	Voc
port diagnostics actatistics Packet Size	Yes
statistics Packet Size	Yes
statistics packet type	Yes
• error statistics	Yes
• SysLog	Yes
product functions / VLAN	
product function	
VLAN - port based	Yes
number of VLANs / maximum	257
number of VLANs - dynamic / maximum	257
number of VLANs / at ring redundancy (HRP; MRP; standby link)	257
product functions / DHCP	
product function	
DHCP client	Yes
product functions / redundancy	160
	Vac
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
product function	Ven
 media redundancy protocol (MRP) with redundancy manager 	Yes
Media Redundancy Protocol Interconnection (MRP-I)	Yes
of the PROFINET IO device / is supported / PROFINET	No
system redundancy	

ring redundancy	Yes
 high speed redundancy protocol (HRP) with redundancy manager 	Yes
 high speed redundancy protocol (HRP) with standby redundancy 	Yes
redundancy procedure STP	Yes
redundancy procedure RSTP	Yes
redundancy procedure RSTP+	Yes
 Parallel Redundancy Protocol (PRP)/operation in the 	Yes
PRP-network	
passive listening	Yes
product functions / security	
product function	
■ IEEE 802.1x (radius)	Yes
 RADIUS client 	Yes
 broadcast/multicast/unicast limiter 	Yes
broadcast blocking	Yes
protocol / is supported	
• SSH	Yes
• SSL	Yes
product functions / time	
product function	
SICLOCK support	Yes
NTP-client	Yes
SNTP client	Yes
protocol / is supported	
• SNTP	Yes
standards, specifications, approvals	
certificate of suitability	Von
• CE marking	Yes
KC approval	Yes
Regulatory Compliance Mark (RCM)	Yes
standard	
for EMC interference emission	EN 61000-6-4 (Class A)
• for immunity to EMC	EN 61000-6-2
for safety / from CSA and UL	UL 60950-1 E115352, CSA C22.2 No. 60950-1
standards, specifications, approvals / hazardous environments	
certificate of suitability	
• ATEX	Yes
• UKEX	Yes
• IECEx	Yes
ULhazloc approval	Yes
CCC / for hazardous zone according to GB standard	Yes
FM registration	Yes
standards, specifications, approvals / other	
certificate of suitability	
RoHS conformity	Yes
IT security for industrial automation systems / according to IEC 62443-4-2:2019	Yes
standards, specifications, approvals / Environmental Product De	eclaration
Environmental Product Declaration	Yes
Global Warming Potential [CO2 eq]	1.00
• total	252.5 kg
	252.5 kg
during manufacturing	26.6 kg
during operation	225.28 kg
after end of life	0.6 kg
product functions / general	
MTBF	84 a
reference code	
 according to IEC 81346-2 	KF
 according to IEC 81346-2:2019 	KFE
 according to IEC 81346-2:2019 	KFE

Warranty period

5 a

product function / is supported / identification link

Yes; according to IEC 61406-1:2022

further information / internet links

internet link

• to website: Selection guide for cables and connectors

• to web page: selection aid TIA Selection Tool

• to website: Industrial communication

• to web page: SiePortal

• to website: Image database

• to website: CAx-Download-Manager

• to website: Industry Online Support

https://support.industry.siemens.com/cs/ww/en/view/109766358

https://www.siemens.com/tstcloud

https://www.siemens.com/simatic-net

https://sieportal.siemens.com/

https://www.automation.siemens.com/bilddb

https://www.siemens.com/cax

https://support.industry.siemens.com

security information

security information

Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Approvals / Certificates

General Product Approval



Declaration of Conformity









General Product Approval

EMV

For use in hazardous locations

Miscellaneous

Declaration of Conformity

<u>FM</u>





<u>KC</u>



For use in hazardous locations

Radio Equipment Type Approval Certi-

Environment

Industrial Communication

CCC-Ex

<u>KC</u>

Confirmation

PROFINET

last modified:

8/16/2024

