
EU Declaration of Conformity

Product:	***Lifeline 3 / Lifeline 4 Cable Pull Switches***	
Name and address of the manufacturer: ***Rockwell Automation Inc.*** ***1201 South 2nd Street*** ***Milwaukee, WI 53204*** ***U.S.A.***	*Name and address of the authorised representative:* ***Rockwell Automation NV*** ***Pegasus Park*** ***De Kleetlaan 12A*** ***1831 Diegem*** ***Belgium***	
This declaration of conformity is issued under the sole responsibility of the manufacturer.		
Object of the declaration:	***Allen-Bradley 440E Series*** *(reference the attached list of catalogue numbers)*	
The object of the declaration described above is in conformity with the relevant Union harmonisation legislation:		
2006/42/EC	*Machinery Directive*	*(MD)*
2011/65/EU	*RoHS Directive*	*(RoHS)*
References to the relevant harmonised standards used or references to the other technical specifications in relation to which conformity is declared:		
EN ISO 13850:2015	*Safety of machinery – Emergency stop function – Principles for design*	
EN ISO 13849-1:2015	*Safety of machinery – Safety-related parts of control systems – Part 1: General principles for design*	
EN 60947-5-5:1997 + A1:2005 +A11:2013 + A2:2017	*Low voltage switchgear and controlgear – Part 5-5: Control circuit devices and switching elements – Electrical emergency stop device with mechanical latching function*	
EN IEC 63000:2018	*Technical documentation for the assessment of electrical and electronic products with respect to the restriction of hazardous substances*	
Additional information:		
Person authorised to compile the technical file (MD):	*Authorised representative (see details above).*	
Product Safety Function (MD):	*Cable-actuated emergency stop devices with direct opening action.*	
Signed for and on behalf of the above named manufacturer:		
Place and date of issue:	*Milwaukee, WI USA*	*16-Jun-2021*
Name, function:	*Daniel L. Nachtigall – Technical Leader, Product Compliance Engineering*	
Signature:		

Catalogue number	*Series* [1]	*Description*
Lifeline 3 cable pull switches with reset, 30m span maximum		
440E-D13100		*Cable-actuated E-stop; 2 N.C. safety contacts, 1 N.O. auxiliary contact*
440E-D13106		*Cable-actuated E-stop; 4 N.C. safety contacts*
440E-D13112		*Cable-actuated E-stop; 3 N.C. safety contacts, 1 N.O. auxiliary contact*
440E-D13114		*Cable-actuated E-stop; 3 N.C. safety contacts, 1 N.O. auxiliary contact*
440E-D13118		*Cable-actuated E-stop; 2 N.C. safety contacts, 2 N.O. auxiliary contacts*
440E-D13120		*Cable-actuated E-stop; 2 N.C. safety contacts, 2 N.O. auxiliary contacts*
440E-D13124		*Cable-actuated E-stop; 3 N.C. safety contacts, 1 N.O. auxiliary contact*
440E-D13132		*Cable-actuated E-stop; 2 N.C. safety contacts, 1 N.O. auxiliary contact*
440E-D13136		*Cable-actuated E-stop; 4 N.C. safety contacts*
440E-D21BNYH		*Cable-actuated E-stop; 2 N.C. safety contacts, 2 N.O. auxiliary contacts*
440E-D2NNNYS		*Cable-actuated E-stop; 2 N.C. safety contacts, 2 N.O. auxiliary contacts*

1) Products of the series level indicated, as well as succeeding series levels, are certified. If no series letter or number is given, then all series are certified.

Catalogue number	*Series* [1]	*Description*
Lifeline 4 cable pull switches with reset and E-stop button, 125m span maximum		
440E-L**B****		*Cable-actuated E-stop per Nomenclature*
440E-L13042		*Cable-actuated E-stop; 3 N.C safety contacts, 1 N.O. auxiliary contact*
440E-L13043		*Cable-actuated E-stop; 3 N.C safety contacts, 1 N.O. auxiliary contact*
440E-L13075		*Cable-actuated E-stop; 2 N.C safety contacts, 1 N.O. auxiliary contact*
440E-L13131		*Dual switch, cable-actuated E-stop; 2 N.C safety contacts, 1 N.O. auxiliary contact*
440E-L13131-4P		*Dual switch, cable-actuated E-stop; 2 N.C safety contacts, 1 N.O. auxiliary contact*
440E-L13133		*Cable-actuated E-stop; 2 N.C safety contacts, 2 N.O. auxiliary contacts*
440E-L13135		*Cable-actuated E-stop; 4 N.C safety contacts*
440E-L13137		*Cable-actuated E-stop; 2 N.C safety contacts, 2 N.O. auxiliary contacts*
440E-L13139		*Cable-actuated E-stop; 4 N.C safety contacts*
440E-L13140		*Cable-actuated E-stop; 2 N.C safety contacts, 2 N.O. auxiliary contacts*
440E-L13141		*Cable-actuated E-stop; 3 N.C safety contacts, 1 N.O. auxiliary contact*
440E-L13147		*Cable-actuated E-stop; 4 N.C safety contacts*
440E-L13149		*Cable-actuated E-stop; 4 N.C safety contacts*
440E-L13150		*Cable-actuated E-stop; 3 N.C safety contacts, 1 N.O. auxiliary contact*
440E-L13152		*Cable-actuated E-stop; 3 N.C safety contacts, 1 N.O. auxiliary contact*
440E-L13153		*Cable-actuated E-stop; 2 N.C safety contacts, 2 N.O. auxiliary contacts*
440E-L13155		*Cable-actuated E-stop; 2 N.C safety contacts, 2 N.O. auxiliary contacts*
440E-L13163		*Cable-actuated E-stop; 2 N.C safety contacts, 1 N.O. auxiliary contact*
440E-L13164		*Cable-actuated E-stop; 3 N.C safety contacts, 1 N.O. auxiliary contact*
440E-L13166		*Cable-actuated E-stop; 2 N.C safety contacts, 1 N.O. auxiliary contact*
440E-L13175		*Cable-actuated E-stop; 2 N.C safety contacts, 1 N.O. auxiliary contact*
440E-L13176		*Cable-actuated E-stop; 2 N.C safety contacts, 2 N.O. auxiliary contacts*
440E-L13178		*Cable-actuated E-stop; 3 N.C safety contacts, 1 N.O. auxiliary contact*
440E-L13179		*Cable-actuated E-stop; 3 N.C safety contacts, 1 N.O. auxiliary contact*
440E-L13181		*Cable-actuated E-stop; 4 N.C safety contacts*
440E-L13182		*Cable-actuated E-stop; 4 N.C safety contacts*
440E-L13184		*Cable-actuated E-stop; 2 N.C safety contacts, 2 N.O. auxiliary contacts*
440E-L13186		*Cable-actuated E-stop; 2 N.C safety contacts, 2 N.O. auxiliary contacts*
440E-L13189		*Cable-actuated E-stop; 3 N.C safety contacts, 1 N.O. auxiliary contact*
440E-L13193		*Cable-actuated E-stop; 2 N.C safety contacts, 2 N.O. auxiliary contacts*
440E-L13208		*Dual switch, cable-actuated E-stop; 2 N.C safety contacts, 1 N.O. auxiliary contact*
440E-L13228		*Dual switch, cable-actuated E-stop; 2 N.C safety contacts, 1 N.O. auxiliary contact*
440E-L13229		*Dual switch, cable-actuated E-stop; 2 N.C safety contacts, 1 N.O. auxiliary contact*
440E-L2NNNYS		*Cable-actuated E-stop; 2 N.C safety contacts, 2 N.O. auxiliary contacts*
440E-LRNC400		*Cable-actuated E-stop; 2 N.C safety contacts, 1 N.O. auxiliary contact*
440E-H13070		*Cable-actuated E-stop; 2 N.C safety contacts*

1) If no series number is given, then all series are covered.

Lifeline 4 Nomenclature:

440E-L	2	1	B	T	S	M	NH
1	2	3		4	5	6	7

1	Designates Product Type 440E-L – Lifeline 4 cable-actuated emergency stop device
2	Designates Safety Contact Configuration 2 – 2 N.C. contacts 3 – 3 N.C. contacts 4 – 4 N.C. contacts
3	Designates Auxiliary Contact Configuration 1 – 1 N.O. contact 2 – 2 N.O. contacts N – None
4	Designates Maximum Actuator Span N – 75m maximum T – 125m maximum
5	Designates Housing Material S – Stainless steel Y – Zinc alloy
6	Designates Connection Type M – Metric conduit H – 8-Pin Micro (M12 L – 12-Pin M23 R – NPT conduit with reset S – 5-Pin Micro (M12) T – North American (NPT) conduit
7	Designates Optional Special Features Blank – No additional options NH – No E-stop button provided