KL2408 | Bus Terminal, 8-channel digital output, 24 V DC, 0.5 A, 1-wire connection

Image similar, may contain optional accessories



KL2408 | Bus Terminal, 8-channel digital output, 24 V DC, 0.5 A, 1-wire connection

Product status: regular delivery

The KL2408 digital output terminal connects the binary control signals from the automation unit on to the actuators at the process level with electrical isolation. It is protected against reverse polarity connection and handles load currents with outputs that are protected against overload and short-circuit. The Bus Terminal contains eight channels which indicate their signal state by means of light emitting diodes. It is particularly suitable for space-saving use in control cabinets. The connection technology is optimized for single-ended inputs. All components have to use the same reference point as the KL2408. The power contacts are looped through. The outputs are supplied by the 24 V power contact.

Product information

Technical data

Technical data	KL2408
Connection technology	1-wire
Number of outputs	8
Nominal voltage	24 V DC (-15%/+20%)
Load type	resistive, inductive, lamp load
Max. output current	0.5 A (short-circuit proof) per channel
Short-circuit current	< 2 A

Technical data	KL2408
Switching-off energy	< 150 mJ/channel
Reverse polarity protection	yes
Electrical isolation	500 V (K-bus/field potential)
Current consumption power contacts	typ. 60 mA + load
Current consumption K-bus	typ. 18 mA
Bit width in the process image	8 outputs
Configuration	no address or configuration setting
Weight	approx. 70 g
Operating temperature	-25...+60°C
Storage temperature	-40...+85°C
Relative humidity	95%, no condensation
Vibration/shock resistance	conforms to EN 60068-2-6/EN 60068-2-27
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4
Protect. rating/installation pos.	IP20/variable
Pluggable wiring level	for all KSxxxx Bus Terminals
Approvals/markings	CE, CCC, UL, ATEX, IECEx, DNV, cFMus
Ex marking	ATEX: II 3G Ex ec IIC T4 Gc IECEx: Ex ec IIC T4 Gc cFMus: Class I, Division 2, Groups A, B, C, D Class I, Zone 2, AEx ec IIC T4 Gc

Housing data	KL-12-8pin	KS-12-8pin
Design form	compact terminal housing with signal LEDs	terminal housing with pluggable wiring level
Material	polycarbonate	
Installation	on 35 mm DIN rail, conforming to EN 60715 with lock	
Side by side mounting by means of	double slot and key connection	
Marking	labeling of the BZxxxx series	
Wiring	solid conductor (s), flexible conductor (st) and ferrule (f): spring actuation by screwdriver	
Connection cross-section	s*: 0.08...2.5 mm^2, st*: 0.08...2.5 mm^2, f*: 0.14...1.5 mm^2	s*: 0.08...1.5 mm^2, st*: 0.08...1.5 mm^2, f*: 0.14...1.5 mm^2
Connection cross-section AWG	s*: AWG28...14, st*: AWG28...14, f*: AWG26...16	s*: AWG28...16, st*: AWG28...16, f*: AWG26...16
Stripping length	8...9 mm	9...10 mm

Housing data	KL-12-8pin	KS-12-8pin
Current load power contacts	I_{max}: 10 A	
Dimensions (W x H x D)	12 mm x 100 mm x 68 mm	

*s: solid wire; st: stranded wire; f: with ferrule

Ordering information

Ordering information	
KL2408	Bus Terminal, 8-channel digital output, 24 V DC, 0.5 A, 1-wire connection
KS2408	Bus Terminal, 8-channel digital output, 24 V DC, 0.5 A, 1-wire connection, pluggable wiring level

Material Compliance

Material compliance	KL2408
REACH SVHC	no
POP	compliant
RoHS	compliant with exemption
RoHS exemption	7c-I: Lead-containing electrical and electronic components in glass and ceramic materials, excluding dielectric ceramics in capacitors
China-RoHS	www.beckhoff.com/china-rohs-io
CA Prop65	www.beckhoff.com/prop65
Disclaimer	This statement and the information contained above are, to the best of our knowledge and belief, accurate, based on the information we have received from our suppliers. This information is in line with the current standard of technology and our suppliers' technical documentation. The absence of the substances is not verified by Beckhoff Automation by means of analytical tests. When addressed to our customers any information contained in this document is subject to the terms and conditions expressed in the governing customer agreement. Our general terms and conditions apply.