KombiSIGN 71 / Permanent Beacon 641

# KS71 Perm. light 12-230VAC/DC RD



| | |
|---|---|
| **Part No.:** | **641.100.00** |
| **Series:** | **KombiSIGN 71** |

| MECHANICAL DATA | |
|---|---|
| Height | 66 mm |
| Diameter | 70 mm |
| Materials | PC |
| Dome colour | Red |
| Protection category | IP65 |
| Tension relief | Not present |
| Working temperature minimum | -20°C |
| Working temperature maximum | +50°C |
| Weight with packaging | 72 g |
| Product weight | 57 g |

| ELECTRICAL DATA | |
|---|---|
| Operating voltage | 12-230V |
| Operating voltage type | AC/DC |
| Protection class | Protection class 2 |
| Pollution degree | 3 |
| Overvoltage category | II |
| insulation voltage | Ui = 250V / Uimp = 2500V |
| Power illuminant | max. 5W |

| OPTICAL DATA | |
|---|---|
| Light source | Filament lamp |
| Light colour | Red |
| Optical signal image | Permanent |
| Service life optical | depends on bulb |
| Lamp fitting/socket | B15d |

| APPROVAL DATA | |
|---|---|
| Conforms with CE | Yes |
| Conforms with RoHS directive | Yes |
| WEEE | Yes |
| Conforms with ATEX-directive | No |
| Conforms with CCC | No |
| Conforms with UL | cULus |
| UL Type Rating | Type 12 |
| Conforms with FCC | No |
| Conforms with ISED | No |
| EAC certificate available | No |
| Conforms with UKCA (Importer) | Yes (WERMA (UK) Ltd.) |


! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

KombiSIGN 71 / Permanent Beacon 641

# KS71 Perm. light 12-230VAC/DC RD

| | |
|---|---|
| Conforms with CMIM | No |
| Conforms with AS-I | No |
| ICAO Certification | No |
| Conforms with DNV | No |
| Conforms with RoHS CN | No |
| Conforms with VdS | No |

## DRAWING




! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.