

Reflex Sensor for Roller Conveyor Systems


OPT244-P06

Part Number



- Electronic background suppression
- Energy-saving trough automatic roll cutoff
- Fully encapsulated
- Integrated logic
- Scaled switching distance adjuster

These sensors have been specially designed for use in accumulation roller conveyors. Their compact design allows for installation between rollers below the transport level. They are thus protected against mechanical damage.




Technical Data


Optical Data	
Range	550 mm
Potentiometer min	220...270 mm
Potentiometer center	320...400 mm
Potentiometer max	550...630 mm
Switching Hysteresis	< 15 %
Light Source	Infrared Light
Wave Length	880 nm
Service Life (T = +25 °C)	100000 h
Risk Group (EN 62471)	1
Max. Ambient Light	10000 Lux
Opening Angle	5 °
Electrical Data	
Supply Voltage	18...30 V DC
Current Consumption Sensor (U _b = 24 V)	< 30 mA
Switching Frequency	100 Hz
Response Time	5 ms
Off-Delay	0...2 s
Temperature Drift	< 10 %
Temperature Range	-25...60 °C
Switching Outputs	2
Switching Output Voltage Drop	< 0,8 V
PNP Switching Output/Switching Current	200 mA
Valve or Motor Output/Switching Current	200 mA
Short Circuit Protection	yes
Reverse Polarity Protection	yes
Overload Protection	yes
Logic	yes
Single Discharge	yes
Output Magnetic Valve/Engine	yes
Automatic roll cutoff	yes
Protection Class	III
Mechanical Data	
Setting Method	Potentiometer
Housing Material	Plastic
Full Encapsulation	yes
Degree of Protection	IP65
Connection	M12 × 1; 4-pin
Cable Length	150 cm
PNP NC	
Connection Diagram No.	733
Control Panel No.	OP1
Suitable Connection Technology No.	2 2s
Suitable Mounting Technology No.	420

Complementary Products


Adapter OPT70N, OPT70S, OPT70P



Ctrl. Panel



05 = Switching Distance Adjuster
30 = Switching Status/Contamination Warning



Legend

+	Supply Voltage +
-	Supply Voltage 0 V
~	Supply Voltage (AC Voltage)
A	Switching Output (NO)
$\bar{A}$	Switching Output (NC)
V	Contamination/Error Output (NO)
$\bar{V}$	Contamination/Error Output (NC)
E	Input (analog or digital)
T	Teach Input
Z	Time Delay (activation)
S	Shielding
RxD	Interface Receive Path
TxD	Interface Send Path
RDY	Ready
GND	Ground
CL	Clock
E/A	Output/Input programmable
	IO-Link
PoE	Power over Ethernet
IN	Safety Input
OSSD	Safety Output
Signal	Signal Output
BI-D+/-	Ethernet Gigabit bidirect. data line (A-D)
EN0 RS422	Encoder 0-pulse 0-0 (TTL)

PT	Platinum measuring resistor
nc	not connected
U	Test Input
$\bar{U}$	Test Input inverted
W	Trigger Input
O	Analog Output
O-	Ground for the Analog Output
BZ	Block Discharge
AMV	Valve Output
a	Valve Control Output +
b	Valve Control Output 0 V
SY	Synchronization
E+	Receiver-Line
S+	Emitter-Line
$\pm$	Grounding
SnR	Switching Distance Reduction
Rx+/-	Ethernet Receive Path
Tx+/-	Ethernet Send Path
Bus	Interfaces-Bus A(+)/B(-)
La	Emitted Light disengageable
Mag	Magnet activation
RES	Input confirmation
EDM	Contact Monitoring
ENAR5422	Encoder A/A (TTL)
ENBR5422	Encoder B/B (TTL)


ENa	Encoder A
ENb	Encoder B
AMIN	Digital output MIN
AMAX	Digital output MAX
AOK	Digital output OK
SY In	Synchronization In
SY OUT	Synchronization OUT
OLt	Brightness output
M	Maintenance

Wire Colors according to DIN IEC 757

BK	Black
BN	Brown
RD	Red
OG	Orange
YE	Yellow
GN	Green
BU	Blue
VT	Violet
GY	Grey
WH	White
PK	Pink
GNYE	Green/Yellow

Switching Distance Deviation

Typical characteristic curve based on Kodak white (90 % remission)



Pot. = Potentiometer Setting

dSr = Switching Distance Change

— black 6 % remission

— grey 18 % remission

