Connector Plug M8 × 1; 4-pin

SG07-ME


Part Number




Technical Data

Mechanical Data			
Connection 1	Plug, straight M8 × 1, 4-pin M8: 0,3 Nm		
Connection mode 1			
Torque			
Cable Diameter	3,55 mm		
Wire cross-section	0,140,34 mm ²		
Assembling	Screw Terminal Technology IP67 -4085 °C		
Degree of Protection			
Temperature Range			
Material Sleeve Nut	CuZn, nickel-plated		
Packaging unit	1 Piece		
Connection Diagram No.	S08		
Connection Equipment No.	7s		

• Plug M8 × 1, straight





Leger	d	PT	Platinum measuring resistor	ENAR9422	Encoder A/Ā (TTL)	
+	Supply Voltage +	nc	not connected	ENBR5422	Encoder B/B (TTL)	
-	Supply Voltage 0 V	U	Test Input	ENA	Encoder A	
~	Supply Voltage (AC Voltage)	Ū	Test Input inverted	ENB	Encoder B	
Α	Switching Output (NO)	W	Trigger Input	Amin	Digital output MIN	
Ā	Switching Output (NC)	W-	Ground for the Trigger Input	Амах	Digital output MAX	
V	Contamination/Error Output (NO)	0	Analog Output	Аок	Digital output OK	
⊽	Contamination/Error Output (NC)	0-	Ground for the Analog Output	SY In	Synchronization In	
E	Input (analog or digital)	BZ	Block Discharge	SY OUT	Synchronization OUT	
Т	Teach Input	Awv	Valve Output	OLT	Brightness output	
Z	Time Delay (activation)	а	Valve Control Output +	М	Maintenance	
S	Shielding	b	Valve Control Output 0 V	rsv	reserved	
RxD	Interface Receive Path	SY	Synchronization	Wire Co	Vire Colors according to DIN IEC 757	
TxD	Interface Send Path	SY-	Ground for the Synchronization	BK	Black	
RDY	Ready	E+	Receiver-Line	BN	Brown	
GND	Ground	S+	Emitter-Line	RD	Red	
CL	Clock	÷	Grounding	OG	Orange	
E/A	Output/Input programmable	SnR	Switching Distance Reduction	YE	Yellow	
②	IO-Link	Rx+/-	Ethernet Receive Path	GN	Green	
PoE	Power over Ethernet	Tx+/-	Ethernet Send Path	BU	Blue	
IN	Safety Input	Bus	Interfaces-Bus A(+)/B(-)	VT	Violet	
OSSD	Safety Output	La	Emitted Light disengageable	GY	Grey	
Signal	Signal Output	Mag	Magnet activation	WH	White	
	Ethernet Gigabit bidirect, data line (A-D)	RES	Input confirmation	PK	Pink	
	Encoder 0-pulse 0-0 (TTL)	EDM	Contactor Monitoring	GNYE	Green/Yellow	