





CE

**Model Number**

GT3,0 50.000/0768

**Features**

- 3 mm slot width

**Connection****Dimensions****Technical Data****General specifications**

Switching element function	PNP	NC
Slot width	3 mm	
Depth of immersion (lateral)	5 ... 7 typ. 6 mm	
Installation		
Output polarity	DC	

**Nominal ratings**

Operating voltage	$U_B$	10 ... 30 V
Switching frequency	$f$	0 ... 2000 Hz
Reverse polarity protected	reverse polarity protected	
Short-circuit protection	pulsing	
Operating current	$I_L$	0 ... 200 mA
No-load supply current	$I_0$	≤ 15 mA
Indication of the switching state	LED, yellow	

**Ambient conditions**

Ambient temperature	-25 ... 70 °C (-13 ... 158 °F)
---------------------	--------------------------------

**Mechanical specifications**

Core cross-section	3 x 0.14 mm <sup>2</sup>
Housing material	PA 6.6
Protection degree	IP67

**Compliance with standards and directives**

Standard conformity	
Standards	EN 60947-5-2:2007 IEC 60947-5-2:2007

**Approvals and certificates**

CCC approval	Products with a maximum operating voltage of ≤36 V do not bear a CCC marking because they do not require approval.
--------------	--