

# Bulk Raw Cable

## CBL-PUR-BK-16x050/3x100-1000M




- Suitable for drag chains and abrasion resistant
- Free of paint wetting interfering substances
- Oil resistant

Cable, PUR/PVC, 19-core black, drag chain suitable, oil resistant



### Dimensions



### Technical Data

<b>Electrical specifications</b>		
Operating voltage	$U_B$	max. 300 V AC/DC
<b>Conformity</b>		
Flammability		DIN EN 50265-2-1
Oil resistance		DIN VDE 0472-803
<b>Ambient conditions</b>		
Ambient temperature		
Cable, fixed		-40 ... 90 °C (-40 ... 194 °F)
Cable, flexing		-5 ... 80 °C (23 ... 176 °F)
Pollution degree		3
<b>Mechanical specifications</b>		
Cable		according to IEC/EN 60228 (DIN VDE 0295) class 6
Sheath diameter		10.5 mm ± 0.2 mm
Bending radius		> 10 x cable diameter, moving > 7.5 x cable diameter, fixed
Sheath color		black (similar to RAL 9005)
Number of cores		19

Release date: 2021-04-09 Date of issue: 2021-04-09 Filename: 199617\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

**PF** PEPPERL+FUCHS

