



Q20NR W/30

► Q20 SERIES INDUSTRY STANDARD GLOBAL HOUSING



WORLD-BEAM Q20 Series: Receiver (Red)

Range: 12 m; Input 10-30V dc

Output: Complementary Solid State NPN

9 m (30 ft) Cable

Part Number: 77792

CERTIFICATIONS



SPECIFICATIONS

Sensing Mode (General)	Opposed
Sensing Mode (Detailed)	Receiver
Housing Style	Rectangular
Primary Housing Material	Thermoplastic
Input/Output	Discrete
Max Sensing Range (mm)	12000
Outputs	NPN
Power Supply/Supply Voltage	10-30 V dc
Connection	9 m Cable
Quick Disconnect Type	No QD
Sensing Beam	Visible Red LED
Operation	Light/Dark Operate

Max Op. Temp. (°C)	60
Min Op. Temp. (°C)	-20
Output response time (ms)	1 ON/0.6 OFF
Special Feature: Intrinsically Safe	No
Special Feature: Remote Teach	No
Special Feature: Water Detection	No
IP Rating	IP67
Delay at Power-up (ms)	100
Repeatability (µs)	140
Number of Pins	4
NEMA Rating	NEMA 6
Max Op. Relative Humidity [%]	95% @ 50°C
Adjustments	N/A
Barrel Diameter (mm)	N/A
Indicator	LEDs
Opposed Mode Emitter/Receiver	Receiver
Feature: Timing (Hold/Delay)	No
Feature: Encapsulated	No
Feature: Hazardous Area	No
Feature: Audible	No








RECOMMENDED PRODUCTS

ADAPTERS, BRACKETS, CLAMPS AND MOUNTING ACCESSORIES


	<p>SMBQ20LV</p> <p>Bracket:Right-angle bracket; +/- 10 deg tip; Stainless Steel; Used with Q20</p>
	<p>SMBQ20L</p> <p>SMBQ20L MOUNTING BRACKET ASSY</p>

	SMBQ20U
	Bracket: Protective bracket; +/- 22.5 deg swivel; Stainless Steel; Used with Q20
	SMBQ20H
	SMBQ20H MOUNTING BRACKET ASSY

APERTURES

	APQ20-0.5
	APQ20-0.5 - QTY 2
	APQ20-1
	APQ20-1 - QTY 2
	APQ20-2
	APQ20-2 - QTY 2
	APQ20-0.5V
	APQ20-0.5V - QTY 2
	APQ20-1V
	APQ20-1V - QTY 2
	APQ20-2V
	APQ20-2V - QTY 2
	APK-Q20
	APK-Q20 - QTY 12

ACCESSORIES

	PFQ20-V
	PFQ20-V FILTER PAIR Q20 VERT



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America