

# **Q20NRL W/30**

## Q20 SERIES INDUSTRY STANDARD GLOBAL HOUSING



WORLD-BEAM Q20 Series: Long Range Receiver (IR)

Range: 20 m; Input 10-30V dc

Output: Complementery Solid State NPN

9 m (30 ft) Cable

Part Number: 78277

## CERTIFICATIONS



## **SPECIFICATIONS**

Sensing Mode (General)	Opposed
Sensing Mode (Detailed)	Receiver
Housing Style	Rectangular
Primary Housing Material	Thermoplastic
Input/Output	Discrete
Max Sensing Range (mm)	20000
Outputs	NPN
Power Supply/Supply Voltage	10-30 V dc
Connection	9 m Cable
Quick Disconnect Type	No QD
Sensing Beam	Infrared LED

Operation	Light/Dark Operate
Max Op. Temp. (°C)	60
Min Op. Temp. (°C)	-20
Output response time (ms)	1 ON/0.6 OFF
Special Feature: Intrinsically Safe	No
Special Feature: Remote Teach	No
Special Feature: Water Detection	No
IP Rating	IP67
Delay at Power-up (ms)	100
Repeatability (µs)	140
Number of Pins	4
NEMA Rating	NEMA 6
Max Op. Relative Humidity [%]	95% @ 50°C
A d j u s t m e n t s	N/A
Barrel Diameter (mm)	N/A
Indicator	LEDs
Opposed Mode Emitter/Receiver	Receiver
Feature: Timing (Hold/Delay)	No
Feature: Encapsulated	No
Feature: Hazardous Area	No
Feature: Audible	No

## RECOMMENDED PRODUCTS

# ADAPTERS, BRACKETS, CLAMPS AND MOUNTING ACCESSORIES



### SMBQ20LV

Bracket:Right-angle bracket; +/- 10 deg tip; Stainless Steel; Used with Q20



## SMBQ20L

SMBQ20L MOUNTING BRACKET ASSY



## **APERTURES**



### **ACCESSORIES**





Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America