



Q20EL

Q20 SERIES INDUSTRY STANDARD GLOBAL HOUSING



WORLD-BEAM Q20 Series: Long Range Emitter (IR)
Range: 20 m; Input 10-30V dc
Output: No output
2 m (6.5 ft) Cable
Part Number: 78159

CERTIFICATIONS



SPECIFICATIONS

Sensing Mode (General)	Opposed
Sensing Mode (Detailed)	Emitter
Housing Style	Rectangular
Primary Housing Material	Thermoplastic
Input/Output	Discrete
Max Sensing Range (mm)	20000
Power Supply/Supply Voltage	10-30 V dc
Connection	2 m Cable
Quick Disconnect Type	No QD
Sensing Beam	Infrared LED
Operation	N/A
Max Op. Temp. (°C)	60

Min Op. Temp. (°C)	-20
Output response time (ms)	N/A
Special Feature: Intrinsically Safe	No
Special Feature: Remote Teach	No
Special Feature: Water Detection	No
IP Rating	IP67
Delay at Power-up (ms)	100
Repeatability (µs)	140
Number of Pins	4
NEMA Rating	NEMA 6
Max Op. Relative Humidity [%]	95% @ 50°C
Adjustments	N/A
Barrel Diameter (mm)	N/A
Indicator	LEDs
Opposed Mode Emitter/Receiver	Emitter
Feature: Timing (Hold/Delay)	No
Feature: Encapsulated	No
Feature: Hazardous Area	No
Feature: Audible	No

RECOMMENDED PRODUCTS

ADAPTERS, BRACKETS, CLAMPS AND MOUNTING ACCESSORIES

	SMBQ20LV Bracket: Right-angle bracket; +/- 10 deg tip; Stainless Steel; Used with Q20
	SMBQ20L SMBQ20L MOUNTING BRACKET ASSY
	SMBQ20U Bracket: Protective bracket; +/- 22.5 deg swivel; Stainless Steel; Used with Q20

	SMBQ20H SMBQ20H MOUNTING BRACKET ASSY
--	---

APERTURES

	APQ20-0.5 APQ20-0.5 - QTY 2
	APQ20-1 APQ20-1 - QTY 2
	APQ20-2 APQ20-2 - QTY 2
	APQ20-0.5V APQ20-0.5V - QTY 2
	APQ20-1V APQ20-1V - QTY 2
	APQ20-2V APQ20-2V - QTY 2
	APK-Q20 APK-Q20 - QTY 12

ACCESSORIES

	PFQ20-V PFQ20-V FILTER PAIR Q20 VERT
---	--



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America

