



QS18EN6CV15QPMA

► QS18 SERIES ALL PURPOSE PHOTOELECTRIC SENSOR



WORLD-BEAM QS18 Expert Series; Convergent

Range: 16 mm; Input: 10-30V dc

Output: NPN

150mm Pigtail Euro Quick-Disconnect Connector

Part Number: 80838

CERTIFICATIONS



SPECIFICATIONS

Sensing Mode (General)	Proximity
Sensing Mode (Detailed)	Convergent
Housing Style	Rectangular w/M18 Mount
Primary Housing Material	Thermoplastic
Input/Output	Discrete
Max Sensing Range (mm)	16
Outputs	NPN
Power Supply/Supply Voltage	10-30 V dc
Connection	Pigtail PUR QD
Quick Disconnect Type	M12 (Euro)
Sensing Beam	Visible Red LED


Operation	Light/Dark Operate
Max Op. Temp. (°C)	70
Min Op. Temp. (°C)	-20
Output response time (ms)	0.6
Special Feature: Intrinsically Safe	No
Special Feature: Remote Teach	Yes
Special Feature: Water Detection	No
IP Rating	IP67
Delay at Power-up (ms)	100
Repeatability (µs)	75
Number of Pins	4
NEMA Rating	NEMA 6
Max Op. Relative Humidity [%]	95% @ 50°C
Lens Material	PMMA
Adjustments	Teach Button
Barrel Diameter (mm)	18
Indicator	LEDs
Opposed Mode Emitter/Receiver	N/A
Feature: Timing (Hold/Delay)	Yes
Feature: Encapsulated	No
Feature: Hazardous Area	No
Feature: Audible	No
Feature: Chemical Resistant	No
IO Link	No














RECOMMENDED PRODUCTS











SINGLE ENDED CORDSETS











	<p>MQDC-406</p> <p>Euro-style Quick Disconnect Cable; 4-Pin Straight Connector; 2 m (6.5 ft) in Length; Nickel-plated Brass Coupling Nut</p>
	<p>MQDC-406RA</p> <p>Euro-Style Quick Disconnect Cable; 4-Pin Right-Angle Connector; 2 m (6.5 ft) in Length; Nickel-plated brass coupling nut</p>
	<p>MQDC-415</p> <p>Euro-style Quick Disconnect Cable; 4-Pin Straight Connector; 5 m (15 ft) in Length; Nickel-plated Brass Coupling Nut.</p>
	<p>MQDC-415RA</p> <p>Euro-Style Quick Disconnect Cable; 4-Pin Right-Angle Connector; 5 m (15 ft) in Length; Nickel-plated brass coupling nut</p>
	<p>MQDC-430</p> <p>Euro-style Quick Disconnect Cable; 4-Pin Straight Connector; 9 m (30 ft) in Length; Nickel-plated Brass Coupling Nut</p>
	<p>MQDC-430RA</p> <p>Euro-Style Quick Disconnect Cable; 4-Pin Right-Angle Connector; 9 m (30 ft) in Length; Nickel-plated brass coupling nut</p>
	<p>MQDC-450</p> <p>Euro-Style Quick Disconnect Cable; 4-Pin Straight Connector; 15 m (50 ft) in Length; Nickel-plated Brass Coupling Nut</p>
	<p>MQDC-450RA</p> <p>Euro-Style Quick Disconnect Cable; 4-Pin Right-Angle Connector; 15 m (50 ft) in Length; Nickel-plated brass coupling nut</p>

ADAPTERS, BRACKETS, CLAMPS AND MOUNTING ACCESSORIES

	<p>SMB18A</p> <p>Bracket: 18 mm Right Angle-mount; Material: 11 Gauge Stainless Steel; Curved mounting slot for versatility/orientation ; Clearance for M4 #8 hardware</p>
	<p>SMB18SF</p> <p>Bracket: 18 mm Swivel; Material: Black VALOX; Mounting Flange; Swivel Locking Hardware Included</p>
	<p>SMB312S</p> <p>Bracket: Side Mounting; Material: Stainless Steel 2-axis</p>

	<p>SMB18FA</p> <p>Bracket: Kit for 12 mm (1/2 in.) Rod Bracket Systems for; most 18 mm barrel mount sensors; lights; and brackets; Includes 3/8-16 X 2 in. Socket Head Cap Screw (SHCS)</p>
	<p>SMB312PD</p> <p>Bracket: 18 mm Barrel Mounting; Material: Stainless Steel</p>
	<p>SMB18S</p> <p>Bracket: 18 mm Swivel; Material: Black VALOX; 18 mm swivel; Hardware included</p>
	<p>SMBQS18Y</p> <p>SMBQS18Y MOUNTING BRACKET ASSY</p>
	<p>SMB18UR</p> <p>Bracket: 2 part universal rotating stainless steel; Allows full horizontal movement; Allows full vertical movement</p>
	<p>SMBQS18A</p> <p>SMBQS18A MOUNTING BRACKET ASSY</p>
	<p>SMB3018SC</p> <p>Bracket: 18 mm swivel barrel or side mounting; Black reinforced thermoplastic polyester; Hardware included</p>
	<p>SMB30SUS</p> <p>Bracket: Side Mounting Swivel; Extended range of motion; Black thermoplastic polyester; Allows Maximum Articulation</p>
	<p>SMBAMS18RA</p> <p>Bracket: Right-angle SMBAMS series with; 18 mm hole for mounting sensors; Articulation slots for 90 plus degree rotation; 12-ga. (2.6 mm) Cold-rolled Steel</p>
	<p>SMB46L</p> <p>Bracket: L; Material: 14 Gauge 316 Stainless Steel</p>
	<p>SMBAMS18P</p> <p>Bracket: Flat SMBAMS series with 18 mm ; hole for mounting sensors; Articulation slots for 90 plus degree rotation; 12-ga. (2.6 mm) Cold-rolled Steel</p>
	<p>SMB18Q</p> <p>Bracket: 18 mm Angled Flanged-Mount; Material: 12 Guage Stainless Steel; Barrel-Mount</p>
	<p>SMB30SK</p> <p>Bracket: Flat mount swivel with extended range; Allows full articulation; Black thermoplastic polyester & 316 stainless steel; Hardware included</p>

	<p>SMB46A</p> <p>Bracket: Adjustable; Stainless Steel; Includes: 2 mm shortarm hex keys</p>
	<p>SMB18AFA</p> <p>Bracket: Covered Mounting Bracket</p>
	<p>SMB18C</p> <p>Bracket: Stainless Steel Mounting; Material: Black VALOX; 18mm split clamp ; Hardware included</p>
	<p>SMB18FAM10</p> <p>Bracket: Kit for 10 mm (3/8 in) Rod Bracket Systems for; most 18 mm barrel mount sensors; lights; and brackets; Includes M10-1.5 X 50 mm Socket Head Cap Screw (SHCS)</p>
	<p>SMB46U</p> <p>Bracket: U; Material: 14 Gauge 316 Stainless Steel</p>
	<p>SMBQS18RA</p> <p>SMBQS18RA MOUNTING BRACKET</p>
	<p>SMB4050YL</p> <p>SMB4050YL MOUNTING BRACKET ASSY W/REPLACEABLE LENS COVER</p>
	<p>SMB46S</p> <p>Bracket: S; Material: 14 Gauge 316 Stainless Steel</p>
	<p>SMB18FM</p> <p>SMB18FM FLANGE MOUNT 18MM BRACKET KIT</p>
	<p>SMB18WT</p> <p>Bracket: 2 part universal rotating stainless steel; Allows full horizontal/vertical movement, modified for DS18 AC models</p>
	<p>SMB1812SF</p> <p>Bracket: Swivel; Compact 12mm; Black reinforced thermoplastic polyester; Hardware included</p>
	<p>SMB18FAB</p> <p>SMB18FAB MOUNTING BRACKET; 121704</p>
	<p>SMB18SM</p> <p>Bracket: Mounts by its base; Material: Black VALOX; Flexible and Convenient ; Hardware included</p>
	<p>SMB18RAVK</p> <p>SMB18RAVK 18MM BRACKET ASSY</p>

	<p>SMB C18</p> <p>Bracket: 28 mm Creform Mounting ; Material: Plastic; For 18 mm Lights and Sensors</p>
	<p>SMB18AFAM10</p> <p>Bracket: Covered Mounting Bracket with 10 mm Screw</p>
	<p>SMB18ATFA</p> <p>SMB18ATFA COVERED MOUNTING BRACKET, 115MM LONG 4 MOUNTING HOLES</p>
	<p>SMBQS18DIN</p> <p>SMBQS18DIN MOUNTING BRACKET ASSY</p>
	<p>SMBQS18WRS</p> <p>SMBQS18WRS</p>
	<p>SMB18UR-2</p> <p>SMB18UR-2 MOUNTING BRKT. ASSY</p>
	<p>SMB18ATFAM10</p> <p>SMB18ATFAM10 COVERED MOUNTING BRACKET,115MM LONG 4 MOUNTING HOLES, W/10MM SCREW</p>
	<p>SMB18AZ</p> <p>SMB18AZ MOUNTING BRACKET ASSY METAL BRACKET CHINA ONLY</p>
	<p>SMB18FVK</p> <p>SMB18FVK 18MM BRACKET ASSY</p>
	<p>SMB18URZ</p> <p>SMB18URZ MOUNTING BRACKET ASSY CHINA ONLY</p>



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America

