



M12PFF25 W/30

► M12 SERIES METAL 12MM BARREL-MOUNT SENSOR



Range: 25 mm; Input 10-30V dc

Part Number: 77212

CERTIFICATIONS



SPECIFICATIONS

| | |
|------------------------------------|--------------------------------|
| Sensing Mode (General) | Proximity |
| Sensing Mode (Detailed) | Background Suppression (Fixed) |
| Housing Style | Barrel |
| Primary Housing Material | Nickel-Plated Brass |
| Input/Output | Discrete |
| Max Sensing Range (mm) | 25 |
| Outputs | PNP |
| Power Supply/Supply Voltage | 10-30 V dc |
| Connection | 9 m Cable |
| Quick Disconnect Type | No QD |
| Sensing Beam | Visible Red LED |
| Operation | Light/Dark Operate |
| Max Op. Temp. (°C) | 60 |

| | |
|--|---------------------------------|
| Min Op. Temp. (°C) | -20 |
| Output response time (ms) | 0.5 |
| Special Feature: Intrinsically Safe | No |
| Special Feature: Remote Teach | No |
| Special Feature: Water Detection | No |
| IP Rating | IP67, IP68 |
| Sensing Beam Wavelength | 680 |
| Delay at Power-up (ms) | 100 |
| Repeatability (µs) | 95 |
| Number of Pins | 4 |
| NEMA Rating | NEMA 5, 6 and 1200 PSI Washdown |
| Max Op. Relative Humidity [%] | 90% @ 50°C |
| Lens Material | PMMA |
| Adjustments | N/A |
| Barrel Diameter (mm) | 12 |
| Indicator | LEDs |
| Opposed Mode Emitter/Receiver | N/A |
| Feature: Washdown Rated | Yes |
| Feature: Timing (Hold/Delay) | No |
| Feature: Encapsulated | Yes |
| Feature: Hazardous Area | No |
| Feature: Audible | No |


RECOMMENDED PRODUCTS

ADAPTERS, BRACKETS, CLAMPS AND MOUNTING ACCESSORIES



SMBQS12PD

Bracket: 12 mm Nose-mount; 16 gauge stainless steel

| | |
|---|---|
|  | <p>SMB12MM</p> <p>Bracket: Right Angle for 12mm threads; Material: 12 Gauge Stainless Steel; (+/-) 10 lateral movement ; Holes accommodate #8 hardware</p> |
|  | <p>SMB12FA</p> <p>Bracket: Kit for 12 mm (1/2 in) Rod Bracket Systems for; most 12 mm barrel mount sensors; lights; and brackets; Includes 3/8-16 X 2 in. Socket Head Cap Screw (SHCS)</p> |
|  | <p>SMB12FAM10</p> <p>Bracket: Kit for 10 mm (3/8 in) Rod Bracket Systems for; most 12 mm barrel mount sensors; lights; and brackets; Includes M10-1.5 X 50 mm Socket Head Cap Screw (SHCS)</p> |



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America