



## Q60VR3LAF1400 W/30

### ► Q60 SERIES 2 M RANGE ADJUSTABLE-FIELD SENSOR



Range: 200-1400 mm; Input: 12-250V dc or 24-250V a

Part Number: 71891

#### CERTIFICATIONS



#### SPECIFICATIONS

<b>Sensing Mode (General)</b>	Proximity
<b>Sensing Mode (Detailed)</b>	Background Suppression (Adjustable)
<b>Housing Style</b>	Rectangular
<b>Primary Housing Material</b>	Thermoplastic
<b>Laser Classification</b>	Class 1
<b>Input/Output</b>	E/M Relay
<b>Max Sensing Range (mm)</b>	1400
<b>Outputs</b>	SPDT e/m Relay
<b>Power Supply/Supply Voltage</b>	12-250 V dc or 24-250 V ac
<b>Connection</b>	9 m Cable
<b>Quick Disconnect Type</b>	No QD

<b>Sensing Beam</b>	Laser
<b>Operation</b>	Light/Dark Operate
<b>Max Op. Temp. (°C)</b>	45
<b>Min Op. Temp. (°C)</b>	-10
<b>Output response time (ms)</b>	15
<b>Special Feature: Intrinsically Safe</b>	No
<b>Special Feature: Remote Teach</b>	No
<b>Special Feature: Water Detection</b>	No
<b>IP Rating</b>	IP67
<b>Delay at Power-up (ms)</b>	1000
<b>Repeatability (µs)</b>	500
<b>Number of Pins</b>	4
<b>NEMA Rating</b>	NEMA 6
<b>Max Op. Relative Humidity [%]</b>	90% @ 50°C
<b>Lens Material</b>	Acrylic
<b>Adjustments</b>	Screw Adjustment
<b>Barrel Diameter (mm)</b>	N/A
<b>Indicator</b>	LEDs
<b>Opposed Mode Emitter/Receiver</b>	N/A
<b>Feature: Timing (Hold/Delay)</b>	Yes
<b>Feature: Encapsulated</b>	No
<b>Feature: Hazardous Area</b>	No
<b>Feature: Audible</b>	No






## RECOMMENDED PRODUCTS

### ADAPTERS, BRACKETS, CLAMPS AND MOUNTING ACCESSORIES



#### **SMBQ60-RIGHT-ANGLE-BRACKET**

Bracket: Right Angle Bracket for Q60

	<p><b>SMBAMSQ60P</b></p> <p>Bracket: Flat SMBAMS series for mounting Q60; Articulation slots for 90 plus degree rotation; 12-ga. 300 series Stainless Steel</p>
	<p><b>SMBAMSQ60IP</b></p> <p>Bracket: Industrial protection SMBAMS series bracket; for Q60 with replaceable window; Articulation slots for 90 plus degree rotation; 12-ga. (2.6 mm) 300 series Stainless Steel</p>
	<p><b>SMBQ60IP</b></p> <p>SMBQ60IP BRACKET ASSEMBLY INDUSTRIAL PROTECTION Q60</p>
	<p><b>SMBQ60-76815</b></p> <p>Bracket: Front Right 45 deg; Includes hardware</p>
	<p><b>SMBQ60-76816</b></p> <p>Bracket: Front Left 45 degree bracket and hardware</p>



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America