

# **QS18VP6DQ1**

### PRODUCTS FOR INDUSTRIAL AUTOMATION



QS18VP6DQ16IN4PINTHDPICO

Part Number: 75382

#### CERTIFICATIONS





#### **SPECIFICATIONS**

Sensing Mode (General)	Proximity
Sensing Mode (Detailed)	Diffuse
Housing Style	Rectangular w/M18 Mount
Primary Housing Material	Thermoplastic
Input/Output	Discrete
Max Sensing Range (mm)	450
Outputs	PNP
Power Supply/Supply Voltage	10-30 V dc
Connection	Pigtail QD
Quick Disconnect Type	M8 (Pico)
Sensing Beam	Infrared LED
Operation	Light/Dark Operate
Max Op. Temp. (°C)	70

	• •
Min Op. Temp. (°C)	-20
Output response time (ms)	0.6
Special Feature: Intrinsically Safe	No
Special Feature: Remote Teach	No
Special Feature: Water Detection	No
IP Rating	IP67
Delay at Power-up (ms)	100
Repeatability (μs)	150
Number of Pins	4
NEMA Rating	NEMA 6
Max Op. Relative Humidity [%]	95% @ 50°C
Lens Material	Acrylic
Adjustments	Potentiometer
Barrel Diameter (mm)	18
Indicator	LEDs
Opposed Mode Emitter/Receiver	N/A
Feature: Timing (Hold/Delay)	No
Feature: Encapsulated	No
Feature: Hazardous Area	No
Feature: Audible	No
Feature: Audible Feature: Chemical Resistant	No No


### **RECOMMENDED PRODUCTS**

## ADAPTERS, BRACKETS, CLAMPS AND MOUNTING ACCESSORIES



#### SMB3125

Bracket: Side Mounting; Material: Stainless Steel 2-axis





Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America

SMBQS18DIN MOUNTING BRACKET ASSY