

Q60BB6LAF1400QPMA

Q60 SERIES 2 M RANGE ADJUSTABLE-FIELD SENSOR



Q60BB6LAF1400QPMA PUR 5-PIN EURO PGTL Part Number: 72294

CERTIFICATIONS





SPECIFICATIONS

Sensing Mode (General)	Proximity
Sensing Mode (Detailed)	Background Suppression (Adjustable)
Housing Style	Rectangular
Primary Housing Material	Thermoplastic
Laser Classification	Class 1
Input/Output	Discrete
Max Sensing Range (mm)	1400
Outputs	Bipolar (NPN & PNP)
Power Supply/Supply Voltage	10-30 V dc
Connection	Pigtail PUR QD
Quick Disconnect Type	M12 (Euro)
Sensing Beam	Laser
Operation	Light/Dark Operate

Max Op. Temp. (°C)	50
Min Op. Temp. (°C)	-10
Output response time (ms)	2
Special Feature: Intrinsically Safe	No
Special Feature: Remote Teach	Yes
Special Feature: Water Detection	No
IP Rating	IP67
Delay at Power-up (ms)	1000
Repeatability (μs)	500
Number of Pins	5
NEMA Rating	NEMA 6
Max Op. Relative Humidity [%]	90% @ 50°C
Lens Material	Acrylic
Adjustments	Screw Adjustment
Barrel Diameter (mm)	N/A
Indicator	LEDs
Opposed Mode Emitter/Receiver	N/A
Feature: Timing (Hold/Delay)	Yes
Feature: Encapsulated	No
Feature: Hazardous Area	No
Feature: Audible	No

RECOMMENDED PRODUCTS

ADAPTERS, BRACKETS, CLAMPS AND MOUNTING ACCESSORIES




SMBQ60-RIGHT-ANGLE-BRACKET

Bracket: Right Angle Bracket for Q60



SMBAMSQ60P

Bracket: Flat SMBAMS series for mounting Q60; Articulation slots for 90 plus degree rotation; 12-ga. 300 series Stainless Steel





Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America