



Q12RN6FF15Q3

► Q12 SERIES MINIATURE SELF-CONTAINED SENSOR



WORLD-BEAM Q12 Series: Fixed-Field

Range: 15 mm; Input: 10-30 V dc

Output: DO; 1 NPN

Pico 3-pin 6 in Pigtail QD

Part Number: 77100

CERTIFICATIONS




SPECIFICATIONS

Sensing Mode (General)	Proximity
Sensing Mode (Detailed)	Background Suppression (Fixed)
Housing Style	Rectangular
Primary Housing Material	Thermoplastic
Input/Output	Discrete
Max Sensing Range (mm)	15
Outputs	NPN
Power Supply/Supply Voltage	10-30 V dc
Connection	Pigtail QD
Quick Disconnect Type	M8 (Pico)
Sensing Beam	Visible Red LED
Operation	Dark Operate




Max Op. Temp. (°C)	55
Min Op. Temp. (°C)	-20
Output response time (ms)	0.7
Special Feature: Intrinsically Safe	No
Special Feature: Remote Teach	No
Special Feature: Water Detection	No
IP Rating	IP67
Sensing Beam Wavelength	640
Delay at Power-up (ms)	120
Repeatability (µs)	175
Number of Pins	3
Max Op. Relative Humidity [%]	95% @ 50°C
Lens Material	Polycarbonate
Adjustments	N/A
Barrel Diameter (mm)	N/A
Indicator	LEDs
Opposed Mode Emitter/Receiver	N/A
Feature: Timing (Hold/Delay)	No
Feature: Encapsulated	No
Feature: Hazardous Area	No
Feature: Audible	No

RECOMMENDED PRODUCTS




SINGLE ENDED CORDSETS

	MQDEC2-506
Euro-Style Quick Disconnect Cable with Shield; 5-Pin Straight Connector; 2 m (6.5 ft) in Length; Chrome-plated brass coupling nut	







	<p>MQDEC2-506RA</p> <p>Euro-Style Quick Disconnect Cable with Shield; 5-Pin Right-Angle Connector; 2 m (6.5 ft) in Length; Chrome-plated brass coupling nut</p>
	<p>MQDEC2-515</p> <p>Euro-Style Quick Disconnect Cable with Shield; 5-Pin Straight Connector; 5 m (15 ft) in Length; Chrome-plated brass coupling nut</p>
	<p>MQDEC2-515RA</p> <p>Euro-Style Quick Disconnect Cable with Shield; 5-Pin Right-Angle Connector; 5 m (15 ft) in Length; Chrome-plated brass coupling nut</p>
	<p>MQDEC2-530</p> <p>Euro-Style Quick Disconnect Cable with Shield; 5-Pin Straight Connector; 9 m (30 ft) in Length; Chrome-plated brass coupling nut</p>
	<p>MQDEC2-530RA</p> <p>Euro-Style Quick Disconnect Cable with Shield; 5-Pin Right-Angle Connector; 9 m (30 ft) in Length; Chrome-plated brass coupling nut</p>
	<p>MQDEC2-550</p> <p>Euro-Style Quick Disconnect Cable with Shield; 5-Pin Straight Connector; 15 m (50 ft) in Length; Chrome-plated brass coupling nut</p>
	<p>MQDEC2-550RA</p> <p>Euro-Style Quick Disconnect Cable with Shield; 5-Pin Right-Angle Connector; 15 m (50 ft) in Length; Chrome-plated brass coupling nut</p>
	<p>PKG3M-10</p> <p>Pico cable for IP68 Pro Ring Lights; Power and strobe control cable; Female 3-pin pico to flying leads; Cable length: 10 m (32 ft)</p>
	<p>PKG3M-2</p> <p>Threaded Pico-Style Quick Disconnect Cable With; Female 3-Pin Pico to Flying leads; 2 m (6.5 ft) in Length; Threaded Coupling</p>
	<p>PKG3M-5</p> <p>Female 3-pin pico to flying leads; Cable length: 5 m (16 ft)</p>
	<p>PKG3M-7</p> <p>Pico cable for IP68 Pro Ring Lights; Power and strobe control cable; Female 3-pin pico to flying leads; Cable length: 7 m (23 ft)</p>
	<p>PKG3M-9</p> <p>Threaded Pico-Style Quick Disconnect Cable With; Female 3-Pin Pico to Flying leads; 9 m (30 ft) in Length; Threaded Coupling</p>





	<p>PKW3M-2</p> <p>Threaded Pico-Style Quick Disconnect Cable With; Right-Angle 3-Pin 150 mm (6 INCH) Pigtail Connector; 2 m (6.5FT) in Length; Threaded coupling</p>
	<p>PKW3M-5</p> <p>Threaded Pico-Style Quick Disconnect Cable With; Right-Angle 3-Pin 150 mm (6 INCH) Pigtail Connector; 1.5 m (5 ft) in Length; Threaded coupling</p>
	<p>PKW3M-9</p> <p>Threaded Pico-Style Quick Disconnect Cable With; Right-Angle 3-Pin 150 mm (6 INCH) Pigtail Connector; 9 m (30FT) in Length; Threaded Coupling</p>

ADAPTERS, BRACKETS, CLAMPS AND MOUNTING ACCESSORIES

	<p>SMBQ12A</p> <p>Bracket: Right-Angle; Stainless Steel; Used with Q12</p>
	<p>SMBQ12T</p> <p>Bracket: Right-Angle Mount; Stainless Steel: 300 Series; 20 Gauge; Used with Q12</p>
	<p>SMBQ12S</p> <p>Bracket: Side Mount; Stainless Steel; Used with Q12</p>

APERTURES

	<p>APKQ12</p> <p>APKQ12 Q12 APERTURE KIT; KIT CONTAINS 2 OF EACH APQ12 APERTURE: -0.5 -1 ; -1.5 -2 -0.5H -1H -0.5V -1V -4S; 18 UNITS TOTAL - QTY 18</p>
	<p>APQ12-.5</p> <p>APQ12-.5 Q12 APERTURE BULK KIT .5MM ROUND - QTY 10</p>
	<p>APQ12-.5H</p> <p>APQ12-.5H Q12 APERTURE BULK KIT .5MM HOR SLOT - QTY 10</p>
	<p>APQ12-.5V</p> <p>APQ12-.5V Q12 APERTURE BULK KIT .5MM VER SLOT - QTY 10</p>
	<p>APQ12-1</p> <p>APQ12-1 Q12 APERTURE BULK KIT 1MM ROUND - QTY 10</p>
	<p>APQ12-1.5</p> <p>APQ12-1.5 Q12 APERTURE BULK KIT 1.5MM ROUND - QTY 10</p>

	APQ12-1H APQ12-1H Q12 APERTURE BULK KIT 1MM HOR SLOT - QTY 10
	APQ12-1V APQ12-1V Q12 APERTURE BULK KIT 1MM VER SLOT - QTY 10
	APQ12-2 APQ12-2 Q12 APERTURE BULK KIT 2MM ROUND - QTY 10
	APQ12-4S APQ12-4S Q12 APERTURE BULK KIT 4MM SQUARE - QTY 10



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America