



## QS18EN6DQ8-74379

### ▶ PRODUCTS FOR INDUSTRIAL AUTOMATION

**ALERT:** This part is obsolete. Contact Banner Engineering for information about selecting a suitable replacement.



QS18EN6DQ8-74379 WIND THRES BLK/WHT  
REVERSED

Part Number: 74379











### SPECIFICATIONS

<b>Sensing Mode (General)</b>	Proximity
<b>Sensing Mode (Detailed)</b>	Diffuse
<b>Housing Style</b>	Rectangular w/M18 Mount
<b>Primary Housing Material</b>	Thermoplastic
<b>Input/Output</b>	Discrete
<b>Max Sensing Range (mm)</b>	800
<b>Outputs</b>	NPN
<b>Power Supply/Supply Voltage</b>	10-30 V dc
<b>Connection</b>	Integral QD
<b>Quick Disconnect Type</b>	M12 (Euro)

<b>Sensing Beam</b>	Infrared LED
<b>Operation</b>	Light/Dark Operate
<b>Max Op. Temp. (°C)</b>	70
<b>Min Op. Temp. (°C)</b>	-20
<b>Output response time (ms)</b>	0.6
<b>Special Feature: Intrinsically Safe</b>	No
<b>Special Feature: Remote Teach</b>	Yes
<b>Special Feature: Water Detection</b>	No
<b>IP Rating</b>	IP67
<b>Delay at Power-up (ms)</b>	100
<b>Repeatability (µs)</b>	75
<b>Number of Pins</b>	4
<b>NEMA Rating</b>	NEMA 6
<b>Max Op. Relative Humidity [%]</b>	95% @ 50°C
<b>Lens Material</b>	PMMA
<b>Adjustments</b>	Teach Button
<b>Barrel Diameter (mm)</b>	18
<b>Indicator</b>	LEDs
<b>Opposed Mode Emitter/Receiver</b>	N/A
<b>Feature: Timing (Hold/Delay)</b>	Yes
<b>Feature: Encapsulated</b>	No
<b>Feature: Hazardous Area</b>	No
<b>Feature: Audible</b>	No
<b>Feature: Chemical Resistant</b>	No
<b>IO Link</b>	No

## RECOMMENDED PRODUCTS

## ADAPTERS, BRACKETS, CLAMPS AND MOUNTING ACCESSORIES

	<b>SMB312S</b> Bracket: Side Mounting; Material: Stainless Steel 2-axis
	<b>SMBQS18Y</b> SMBQS18Y MOUNTING BRACKET ASSY
	<b>SMBQS18A</b> SMBQS18A MOUNTING BRACKET ASSY
	<b>SMB30SUS</b> Bracket: Side Mounting Swivel; Extended range of motion; Black thermoplastic polyester; Allows Maximum Articulation
	<b>SMB46L</b> Bracket: L; Material: 14 Gauge 316 Stainless Steel
	<b>SMB46U</b> Bracket: U; Material: 14 Gauge 316 Stainless Steel
	<b>SMBQS18RA</b> SMBQS18RA MOUNTING BRACKET
	<b>SMB4050YL</b> SMB4050YL MOUNTING BRACKET ASSY W/REPLACEABLE LENS COVER
	<b>SMB46S</b> Bracket: S; Material: 14 Gauge 316 Stainless Steel
	<b>SMBQS18DIN</b> SMBQS18DIN MOUNTING BRACKET ASSY



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America

