



Q60VR3LAF1400QPMA10


▶ PRODUCTS FOR INDUSTRIAL AUTOMATION



Q60VR3LAF1400QPMA10 6 INCH 5 PIN MINI PUR
PIGTAIL

Part Number: 73449

CERTIFICATIONS





SPECIFICATIONS





Sensing Mode (General)	Proximity
Sensing Mode (Detailed)	Background Suppression (Adjustable)
Housing Style	Rectangular
Primary Housing Material	Thermoplastic
Laser Classification	Class 1
Input/Output	E/M Relay
Max Sensing Range (mm)	1400
Outputs	SPDT e/m Relay
Power Supply/Supply Voltage	12-250 V dc or 24-250 V ac
Quick Disconnect Type	No QD
Sensing Beam	Laser

Operation	Light/Dark Operate
Max Op. Temp. (°C)	45
Min Op. Temp. (°C)	-10
Output response time (ms)	15
Special Feature: Intrinsically Safe	No
Special Feature: Remote Teach	No
Special Feature: Water Detection	No
IP Rating	IP67
Delay at Power-up (ms)	1000
Repeatability (µs)	500
NEMA Rating	NEMA 6
Max Op. Relative Humidity [%]	90% @ 50°C
Lens Material	Acrylic
Adjustments	Screw Adjustment
Barrel Diameter (mm)	N/A
Indicator	LEDs
Opposed Mode Emitter/Receiver	N/A
Feature: Timing (Hold/Delay)	Yes
Feature: Encapsulated	No
Feature: Hazardous Area	No
Feature: Audible	No

RECOMMENDED PRODUCTS

ADAPTERS, BRACKETS, CLAMPS AND MOUNTING ACCESSORIES

	<p>SMBQ60-RIGHT-ANGLE-BRACKET</p> <p>Bracket: Right Angle Bracket for Q60</p>
	<p>SMBAMSQ60P</p> <p>Bracket: Flat SMBAMS series for mounting Q60; Articulation slots for 90 plus degree rotation; 12-ga. 300 series Stainless Steel</p>

	SMBAMSQ60IP Bracket: Industrial protection SMBAMS series bracket; for Q60 with replaceable window; Articulation slots for 90 plus degree rotation; 12-ga. (2.6 mm) 300 series Stainless Steel
	SMBQ60IP SMBQ60IP BRACKET ASSEMBLY INDUSTRIAL PROTECTION Q60
	SMBQ60-76815 Bracket: Front Right 45 deg; Includes hardware
	SMBQ60-76816 Bracket: Front Left 45 degree bracket and hardware



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America