

QS30FF400Q-19870

PRODUCTS FOR INDUSTRIAL AUTOMATION



WORLD-BEAM QS30 Series: Fixed-Field

Fluorescent Immune; Range: 400 mm; Input: 10-30 V

dc

Output: Bipolar: 1 NPN; 1 PNP

Euro-Style Euro M12 5-pin Integral QD

Part Number: 19870

SPECIFICATIONS

Sensing Mode (General)	Proximity
Sensing Mode (Detailed)	Background Suppression (Fixed)
Housing Style	Rectangular w/M30 Mount
Primary Housing Material	Thermoplastic
Input/Output	Discrete
Max Sensing Range (mm)	400
Outputs	Bipolar (NPN & PNP)
Power Supply/Supply Voltage	10-30 V dc
Connection	Integral QD
Quick Disconnect Type	M12 (Euro)
Sensing Beam	Visible Red LED
Operation	Light/Dark Operate
Max Op. Temp. (°C)	70

Min Op. Temp. (°C)	-20
Output response time (ms)	2
Special Feature: Intrinsically Safe	No
Special Feature: Remote Teach	No
Special Feature: Water Detection	No
IP Rating	IP67
Delay at Power-up (ms)	100
Repeatability (μs)	500
Number of Pins	5
NEMA Rating	NEMA 6
Max Op. Relative Humidity [%]	95% @ 50°C
Lens Material	Acrylic
A d j u s t m e n t s	N/A
Barrel Diameter (mm)	30
Indicator	LEDs
Opposed Mode Emitter/Receiver	N/A
Feature: Timing (Hold/Delay)	No
Feature: Encapsulated	No
Feature: Hazardous Area	No
Feature: Audible	No

RECOMMENDED PRODUCTS

ADAPTERS, BRACKETS, CLAMPS AND MOUNTING ACCESSORIES



SMB30MM

Bracket: 30mm; Material: 12 Gauge Stainless Steel; Curved mounting slot for versatility/orientation; Clearance for M6 (1/4 in.) hardware



SMB30SC

Bracket: Compact 30 mm Swivel; Black reinforced thermoplastic polyester; Wide Range of Articulation ; Hardware included



SMB30A

Bracket: Right Angle Mounting; Material: 12 Gauge Stainless Steel; Curved mounting slot for versatility/orientation; Clearance for M6 (1/4 in.) hardware



SMB30S

Bracket: Stainless Steel Mounting; Material: Black Polyester; 30 mm Swivel; Hardware included



SMBAMS30RA

Bracket: 30mm Right Angle; Material: 12 Gauge cold rolled steel; Curved mounting slot for versatility/orientation



SMB30FA

SMB30FA MOUNTING BRACKET



SMB30RAVK

Bracket: V-Clamp Mount; 30 mm hole to 28 mm tube; Right-angle



SMBQS30Y

Bracket: Heavy-duty die-cast bracket M18 vertical mount option; +/- 8 deg tilt adjustment with cabled units; Includes nuts and lock washerr; Used with QS30 (DC only)



SMB30FVK

SMB30FVK 30MM BRACKET ASSY



SMBAMS30P

Bracket: 30 mm flat bracket; Material: 12 Gauge Cold Rolled Steel; Curved mounting slot for versatility/orientation



SMB46L

Bracket: L; Material: 14 Gauge 316 Stainless Steel



SMB30SM

Bracket: Swivel; Material: Black VALOX; Swivel ball is locked when bolts are tightened; Hardware included



SMBQS30LT

Bracket: Tall right-angle bracket for QD models; +/- 8 deg tilt adjustment;14-ga. Stainless Steel; Used with QS30 with Integral QDs



SMB30C

Bracket: Stainless Steel Mounting; Material: Black VALOX; 30mm split clamp; Hardware included



SMBQS30YL

Bracket: Heavy-duty die-cast bracket designed for ; industrial protection; Replaceable window; M18 vertical mount option; Includes nuts and lock washer; Used with QS30 (DC only)



SMB30Q

Bracket: 30 mm Angle Flanged Mounting; For use with Q40 Sensors



SMB46U

Bracket: U; Material: 14 Gauge 316 Stainless Steel



SMB46S

Bracket: S; Material: 14 Gauge 316 Stainless Steel



SMB30FAM10

SMB30FAM10 MOUNTING BRACKET, M10 X 50MM SHCS, M5 X 18MM SHCS



SMBAMS30PL52

SMBAMS30PL52 AUTOMOTIVE BRKT STRAIGHT LEGEND PLATE



SMBAMS30RLS

Bracket: Right Angle; 30 mm hole; Small Legend, Automotive Industry;



SMBAMS30PL52R

Bracket: Flat SMBAMS series with space; for $60 \times 58 \text{ mm}$ label; 30 mm hole for mounting sensors; Articulation slots for 90 plus degree rotation; 12-ga. (2.6 mm) Cold-rolled Steel



SMB30MM-62101

SMB30MM-62101 MNTG BRKT QTY 2 30 MILLIMETER



SMB30RAL52R

Bracket: 30 mm Hole; 8.3 mm X 127 mm Slot; Zinc Plated Cold Rolled Steel



SMBAMS30RAE

Bracket: 30 mm Right Angle extended version; Material: 12 Gauge Cold Rolled Steel; Curved Mounting Slot for versatility/orientation



SMB30FVKQ

Bracket: 30 mm Bracket Assembly

ACCESSORIES



SMB30RAVKQ

Bracket: 30 mm Bracket Assembly



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America