



## QS186LE211Q8-97546

### ▶ PRODUCTS FOR INDUSTRIAL AUTOMATION



WORLD-BEAM QS18 Series: Laser Class 2; Vertical Line

Range: 15 m; Input: 10-30V dc

Vdc on pin2 and Laser enable internally

Output: Not Applicable

Euro-Style Integral Quick-Disconnect

Part Number: 97546

### SPECIFICATIONS

<b>Sensing Mode (General)</b>	Opposed
<b>Sensing Mode (Detailed)</b>	Laser Emitter
<b>Housing Style</b>	Rectangular w/M18 Mount
<b>Primary Housing Material</b>	Thermoplastic
<b>Laser Classification</b>	Class 2
<b>Input/Output</b>	Discrete
<b>Max Sensing Range (mm)</b>	15000
<b>Outputs</b>	N/A
<b>Power Supply/Supply Voltage</b>	10-30 V dc
<b>Connection</b>	Integral QD
<b>Quick Disconnect Type</b>	M12 (Euro)
<b>Sensing Beam</b>	Laser
<b>Operation</b>	N/A

<b>Max Op. Temp. (°C)</b>	50
<b>Min Op. Temp. (°C)</b>	-10
<b>Output response time (ms)</b>	N/A
<b>Special Feature: Intrinsically Safe</b>	No
<b>Special Feature: Remote Teach</b>	No
<b>Special Feature: Water Detection</b>	No
<b>IP Rating</b>	IP67
<b>Sensing Beam Wavelength</b>	650
<b>Delay at Power-up (ms)</b>	10
<b>Repeatability (µs)</b>	N/A
<b>Number of Pins</b>	4
<b>NEMA Rating</b>	NEMA 6
<b>Max Op. Relative Humidity [%]</b>	95% @ 50°C
<b>Lens Material</b>	PMMA
<b>Adjustments</b>	N/A
<b>Barrel Diameter (mm)</b>	18
<b>Indicator</b>	LEDs
<b>Opposed Mode Emitter/Receiver</b>	Emitter
<b>Feature: Timing (Hold/Delay)</b>	No
<b>Feature: Encapsulated</b>	No
<b>Feature: Hazardous Area</b>	No
<b>Feature: Audible</b>	No
<b>Feature: Chemical Resistant</b>	No
<b>IO Link</b>	No



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America