



QS18RWLPQ2

► QS18 SERIES ALL PURPOSE PHOTOELECTRIC SENSOR



WORLD-BEAM QS18 Univ Volt; Polar Retro; Vis Red

Range: 3.5 m; Input: 20 to 140V ac/dc

Output: D.O. P-MOSFET (Sourcing)

150mm Pigtail Micro Pigtail QD Connector

Part Number: 79583

CERTIFICATIONS



SPECIFICATIONS

| | |
|------------------------------------|-------------------------|
| Sensing Mode (General) | Retroreflective |
| Sensing Mode (Detailed) | Polarized |
| Housing Style | Rectangular w/M18 Mount |
| Primary Housing Material | Thermoplastic |
| Input/Output | Discrete |
| Max Sensing Range (mm) | 3500 |
| Outputs | P-MOSFET (Sourcing) |
| Power Supply/Supply Voltage | 20-140 V ac/dc |
| Connection | Pigtail QD |
| Quick Disconnect Type | 1/2 in. (Micro) |
| Sensing Beam | Visible Red LED |

| | |
|--|--------------------|
| Operation | Dark Operate |
| Max Op. Temp. (°C) | 70 |
| Min Op. Temp. (°C) | -25 |
| Output response time (ms) | 8.3 |
| Special Feature: Intrinsically Safe | No |
| Special Feature: Remote Teach | No |
| Special Feature: Water Detection | No |
| IP Rating | IP67 |
| Delay at Power-up (ms) | 100ms dc, 300ms ac |
| Repeatability (µs) | 1500 |
| Number of Pins | 4 |
| NEMA Rating | NEMA 6 |
| Max Op. Relative Humidity [%] | 95% @ 55°C |
| Lens Material | PMMA |
| Adjustments | Potentiometer |
| Barrel Diameter (mm) | 18 |
| Indicator | LEDs |
| Opposed Mode Emitter/Receiver | N/A |
| Feature: Timing (Hold/Delay) | No |
| Feature: Encapsulated | No |
| Feature: Hazardous Area | No |
| Feature: Audible | No |
| Feature: Chemical Resistant | No |
| IO Link | No |














RECOMMENDED PRODUCTS

SINGLE ENDED CORDSETS





| | |
|---|--|
|  | <p>MQAC-406</p> <p>Micro-style Quick Disconnect Cable; 4 Pin Straight Connector; 2 m (6.5 ft) in Length; Chrome plated brass coupling nut</p> |
|  | <p>MQAC-415</p> <p>Micro-style Quick Disconnect Cable; 4 Pin Straight Connector; 5 m (15 ft) in Length; Chrome plated brass coupling nut</p> |
|  | <p>MQAC-430</p> <p>Micro-style Quick Disconnect Cable; 4 Pin Straight Connector; 9 m (30 ft) in Length; Chrome plated brass coupling nut</p> |

ADAPTERS, BRACKETS, CLAMPS AND MOUNTING ACCESSORIES



| | |
|---|--|
|  | <p>SMB18A</p> <p>Bracket: 18 mm Right Angle-mount; Material: 11 Gauge Stainless Steel; Curved mounting slot for versatility/orientation ; Clearance for M4 #8 hardware</p> |
|  | <p>SMB18SF</p> <p>Bracket: 18 mm Swivel; Material: Black VALOX; Mounting Flange; Swivel Locking Hardware Included</p> |
|  | <p>SMB312S</p> <p>Bracket: Side Mounting; Material: Stainless Steel 2-axis</p> |
|  | <p>SMB18FA</p> <p>Bracket: Kit for 12 mm (1/2 in.) Rod Bracket Systems for; most 18 mm barrel mount sensors; lights; and brackets; Includes 3/8-16 X 2 in. Socket Head Cap Screw (SHCS)</p> |
|  | <p>SMB312PD</p> <p>Bracket: 18 mm Barrel Mounting; Material: Stainless Steel</p> |
|  | <p>SMB18S</p> <p>Bracket: 18 mm Swivel; Material: Black VALOX; 18 mm swivel; Hardware included</p> |
|  | <p>SMBQS18Y</p> <p>SMBQS18Y MOUNTING BRACKET ASSY</p> |
|  | <p>SMB18UR</p> <p>Bracket: 2 part universal rotating stainless steel; Allows full horizontal movement; Allows full vertical movement</p> |
|  | <p>SMBQS18A</p> <p>SMBQS18A MOUNTING BRACKET ASSY</p> |

| | |
|---|---|
|  | <p>SMB3018SC</p> <p>Bracket: 18 mm swivel barrel or side mounting; Black reinforced thermoplastic polyester; Hardware included</p> |
|  | <p>SMB30SUS</p> <p>Bracket: Side Mounting Swivel; Extended range of motion; Black thermoplastic polyester; Allows Maximum Articulation</p> |
|  | <p>SMBAMS18RA</p> <p>Bracket: Right-angle SMBAMS series with; 18 mm hole for mounting sensors; Articulation slots for 90 plus degree rotation; 12-ga. (2.6 mm) Cold-rolled Steel</p> |
|  | <p>SMB46L</p> <p>Bracket: L; Material: 14 Gauge 316 Stainless Steel</p> |
|  | <p>SMBAMS18P</p> <p>Bracket: Flat SMBAMS series with 18 mm ; hole for mounting sensors; Articulation slots for 90 plus degree rotation; 12-ga. (2.6 mm) Cold-rolled Steel</p> |
|  | <p>SMB18Q</p> <p>Bracket: 18 mm Angled Flanged-Mount; Material: 12 Gauge Stainless Steel; Barrel-Mount</p> |
|  | <p>SMB30SK</p> <p>Bracket: Flat mount swivel with extended range; Allows full articulation; Black thermoplastic polyester & 316 stainless steel; Hardware included</p> |
|  | <p>SMB46A</p> <p>Bracket: Adjustable; Stainless Steel; Includes: 2 mm shortarm hex keys</p> |
|  | <p>SMB18AFA</p> <p>Bracket: Covered Mounting Bracket</p> |
|  | <p>SMB18C</p> <p>Bracket: Stainless Steel Mounting; Material: Black VALOX; 18mm split clamp ; Hardware included</p> |
|  | <p>SMB18FAM10</p> <p>Bracket: Kit for 10 mm (3/8 in) Rod Bracket Systems for; most 18 mm barrel mount sensors; lights; and brackets; Includes M10-1.5 X 50 mm Socket Head Cap Screw (SHCS)</p> |
|  | <p>SMB46U</p> <p>Bracket: U; Material: 14 Gauge 316 Stainless Steel</p> |
|  | <p>SMBQS18RA</p> <p>SMBQS18RA MOUNTING BRACKET</p> |

| | |
|---|--|
|  | <p>SMB4050YL</p> <p>SMB4050YL MOUNTING BRACKET ASSY W/REPLACEABLE LENS COVER</p> |
|  | <p>SMB46S</p> <p>Bracket: S; Material: 14 Gauge 316 Stainless Steel</p> |
|  | <p>SMB18FM</p> <p>SMB18FM FLANGE MOUNT 18MM BRACKET KIT</p> |
|  | <p>SMB18WT</p> <p>Bracket: 2 part universal rotating stainless steel; Allows full horizontal/vertical movement, modified for DS18 AC models</p> |
|  | <p>SMB1812SF</p> <p>Bracket: Swivel; Compact 12mm; Black reinforced thermoplastic polyester; Hardware included</p> |
|  | <p>SMB18FAB</p> <p>SMB18FAB MOUNTING BRACKET; 121704</p> |
|  | <p>SMB18SM</p> <p>Bracket: Mounts by its base; Material: Black VALOX; Flexible and Convenient ; Hardware included</p> |
|  | <p>SMB18RAVK</p> <p>SMB18RAVK 18MM BRACKET ASSY</p> |
|  | <p>SMBC18</p> <p>Bracket: 28 mm Creform Mounting ; Material: Plastic; For 18 mm Lights and Sensors</p> |
|  | <p>SMB18AFAM10</p> <p>Bracket: Covered Mounting Bracket with 10 mm Screw</p> |
|  | <p>SMB18ATFA</p> <p>SMB18ATFA COVERED MOUNTING BRACKET, 115MM LONG 4 MOUNTING HOLES</p> |
|  | <p>SMBQS18DIN</p> <p>SMBQS18DIN MOUNTING BRACKET ASSY</p> |
|  | <p>SMBQS18WRS</p> <p>SMBQS18WRS</p> |
|  | <p>SMB18UR-2</p> <p>SMB18UR-2 MOUNTING BRKT. ASSY</p> |

| | |
|---|---|
|  | SMB18ATFAM10 |
| | SMB18ATFAM10 COVERED MOUNTING BRACKET,115MM LONG 4 MOUNTING HOLES, W/10MM SCREW |
|  | SMB18AZ |
| | SMB18AZ MOUNTING BRACKET ASSY METAL BRACKET CHINA ONLY |
|  | SMB18FVK |
| | SMB18FVK 18MM BRACKET ASSY |
|  | SMB18URZ |
| | SMB18URZ MOUNTING BRACKET ASSY CHINA ONLY |

RETROREFLECTIVE TARGET

| | |
|--|--|
|  | BRT-2X2 |
| | Retroreflective Target: Rectangular -51x51mm; Reflectivity Factor: 1.0; Max. Temp.= 50 degrees C; Plastic - two screw holes for mounting |
|  | BRT-84 |
| | BRT-84 |



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America