



QS186EBQ8

► QS18 SERIES ALL PURPOSE PHOTOELECTRIC SENSOR



WORLD-BEAM QS18 Series: Emitter (Flush Front)

Range: 3m; Input: 10-30V dc

Output: Not applicable - No outputs

Integral Euro-Style Quick-Disconnect Connector

Part Number: 66448

CERTIFICATIONS



SPECIFICATIONS

Sensing Mode (General)	Opposed
Sensing Mode (Detailed)	Emitter
Housing Style	Rectangular
Primary Housing Material	Thermoplastic
Input/Output	Discrete
Max Sensing Range (mm)	3000
Power Supply/Supply Voltage	10-30 V dc
Connection	Integral QD
Quick Disconnect Type	M12 (Euro)
Sensing Beam	Infrared LED
Operation	N/A

Max Op. Temp. (°C)	70
Min Op. Temp. (°C)	-20
Output response time (ms)	N/A
Special Feature: Intrinsically Safe	No
Special Feature: Remote Teach	No
Special Feature: Water Detection	No
IP Rating	IP67
Delay at Power-up (ms)	100
Repeatability (µs)	100
Number of Pins	4
NEMA Rating	NEMA 6
Max Op. Relative Humidity [%]	95% @ 50°C
Lens Material	Acrylic
Adjustments	N/A
Barrel Diameter (mm)	N/A
Indicator	LEDs
Opposed Mode Emitter/Receiver	Emitter
Feature: Timing (Hold/Delay)	No
Feature: Encapsulated	No
Feature: Hazardous Area	No
Feature: Audible	No
Feature: Chemical Resistant	No
IO Link	No

RECOMMENDED PRODUCTS

SINGLE ENDED CORDSETS

	<p>MQDC-406</p> <p>Euro-style Quick Disconnect Cable; 4-Pin Straight Connector; 2 m (6.5 ft) in Length; Nickel-plated Brass Coupling Nut</p>
	<p>MQDC-406RA</p> <p>Euro-Style Quick Disconnect Cable; 4-Pin Right-Angle Connector; 2 m (6.5 ft) in Length; Nickel-plated brass coupling nut</p>
	<p>MQDC-415</p> <p>Euro-style Quick Disconnect Cable; 4-Pin Straight Connector; 5 m (15 ft) in Length; Nickel-plated Brass Coupling Nut.</p>
	<p>MQDC-415RA</p> <p>Euro-Style Quick Disconnect Cable; 4-Pin Right-Angle Connector; 5 m (15 ft) in Length; Nickel-plated brass coupling nut</p>
	<p>MQDC-430</p> <p>Euro-style Quick Disconnect Cable; 4-Pin Straight Connector; 9 m (30 ft) in Length; Nickel-plated Brass Coupling Nut</p>
	<p>MQDC-430RA</p> <p>Euro-Style Quick Disconnect Cable; 4-Pin Right-Angle Connector; 9 m (30 ft) in Length; Nickel-plated brass coupling nut</p>
	<p>MQDC-450</p> <p>Euro-Style Quick Disconnect Cable; 4-Pin Straight Connector; 15 m (50 ft) in Length; Nickel-plated Brass Coupling Nut</p>
	<p>MQDC-450RA</p> <p>Euro-Style Quick Disconnect Cable; 4-Pin Right-Angle Connector; 15 m (50 ft) in Length; Nickel-plated brass coupling nut</p>

ADAPTERS, BRACKETS, CLAMPS AND MOUNTING ACCESSORIES

	<p>SMB18A</p> <p>Bracket: 18 mm Right Angle-mount; Material: 11 Gauge Stainless Steel; Curved mounting slot for versatility/orientation ; Clearance for M4 #8 hardware</p>
	<p>SMB312S</p> <p>Bracket: Side Mounting; Material: Stainless Steel 2-axis</p>

APERTURES

	APQS18-020 APQS18-020 APERTURE QS18 SERIES - QTY 6
	APQS18-020H APQS18-020H APERTURE QS18 SERIES - QTY 6
	APQS18-020V APQS18-020V APERTURE QS18 SERIES - QTY 6
	APQS18-040 APQS18-040 APERTURE QS18 SERIES QTY 6
	APQS18-040H APQS18-040H APERTURE QS18 SERIES - QTY 6
	APQS18-040V APQS18-040V APERTURE QS18 SERIES - QTY 6
	APQS18-100 APQS18-100 APERTURE QS18 SERIES QTY 6
	APQS18-100H APQS18-100H APERTURE QS18 SERIES QTY 6
	APQS18-100V APQS18-100V APERTURE QS18 SERIES QTY 6
	APQS18-DVHX2 APQS18-DVHX2 APERTURE QS18 SERIES QTY 18



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America

