



QS18VN6LPQ-94778

▶ PRODUCTS FOR INDUSTRIAL AUTOMATION

ALERT: This part is obsolete. Contact Banner Engineering for information about selecting a suitable replacement.



WORLD-BEAM QS18: Polarized Retro
 Range: 3.5 m; Input: 10-30 V dc
 Output: Complementary Solid State NPN
 Pico 16 in Pigtail Quick-Disconnect
 Part Number: 94778

SPECIFICATIONS

Sensing Mode (General)	Retroreflective
Sensing Mode (Detailed)	Polarized
Housing Style	Rectangular w/M18 Mount
Primary Housing Material	Thermoplastic
Input/Output	Discrete
Max Sensing Range (mm)	3500
Outputs	NPN
Power Supply/Supply Voltage	10-30 V dc
Connection	610 mm Pigtail QD
Quick Disconnect Type	M8 (Pico)

Sensing Beam	Visible Red LED
Operation	Light/Dark Operate
Max Op. Temp. (°C)	70
Min Op. Temp. (°C)	-20
Output response time (ms)	0.6
Special Feature: Intrinsically Safe	No
Special Feature: Remote Teach	No
Special Feature: Water Detection	No
IP Rating	IP67
Delay at Power-up (ms)	100
Repeatability (µs)	150
Number of Pins	4
NEMA Rating	NEMA 6
Max Op. Relative Humidity [%]	95% @ 50°C
Lens Material	Acrylic
Adjustments	Potentiometer
Barrel Diameter (mm)	18
Indicator	LEDs
Opposed Mode Emitter/Receiver	N/A
Feature: Timing (Hold/Delay)	No
Feature: Encapsulated	No
Feature: Hazardous Area	No
Feature: Audible	No
Feature: Chemical Resistant	No
IO Link	No



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America