



## QS30VR3LPQP-75059

### ▶ PRODUCTS FOR INDUSTRIAL AUTOMATION



QS30VR3LPQP-75059 6 in 5PIN MINI

Part Number: 75059



### SPECIFICATIONS





|                                    |                            |
|------------------------------------|----------------------------|
| <b>Sensing Mode (General)</b>      | Retroreflective            |
| <b>Sensing Mode (Detailed)</b>     | Polarized                  |
| <b>Housing Style</b>               | Rectangular w/M30 Mount    |
| <b>Primary Housing Material</b>    | Thermoplastic              |
| <b>Input/Output</b>                | E/M Relay                  |
| <b>Max Sensing Range (mm)</b>      | 8000                       |
| <b>Outputs</b>                     | SPDT e/m Relay             |
| <b>Power Supply/Supply Voltage</b> | 12-250 V dc or 24-250 V ac |
| <b>Connection</b>                  | Pigtail QD                 |
| <b>Quick Disconnect Type</b>       | 7/8 in. (Mini)             |
| <b>Sensing Beam</b>                | Visible Red LED            |
| <b>Operation</b>                   | Light/Dark Operate         |
| <b>Max Op. Temp. (°C)</b>          | 70                         |

|  |            |
|--|------------|
| <b>Min Op. Temp. (°C)</b>                  | -20        |
| <b>Output response time (ms)</b>           | 15         |
| <b>Special Feature: Intrinsically Safe</b> | No         |
| <b>Special Feature: Remote Teach</b>       | No         |
| <b>Special Feature: Water Detection</b>    | No         |
| <b>IP Rating</b>                           | IP67       |
| <b>Delay at Power-up (ms)</b>              | 100        |
| <b>Repeatability (µs)</b>                  | N/A        |
| <b>Number of Pins</b>                      | 5          |
| <b>NEMA Rating</b>                         | NEMA 6     |
| <b>Max Op. Relative Humidity [%]</b>       | 95% @ 50°C |
| <b>Lens Material</b>                       | Acrylic    |
| <b>Adjustments</b>                         | N/A        |
| <b>Barrel Diameter (mm)</b>                | 30         |
| <b>Indicator</b>                           | LEDs       |
| <b>Opposed Mode Emitter/Receiver</b>       | N/A        |
| <b>Feature: Timing (Hold/Delay)</b>        | No         |
| <b>Feature: Encapsulated</b>               | No         |
| <b>Feature: Hazardous Area</b>             | No         |
| <b>Feature: Audible</b>                    | No         |

## RECOMMENDED PRODUCTS

### ADAPTERS, BRACKETS, CLAMPS AND MOUNTING ACCESSORIES

|   |  |
|---|--|
|  | <p><b>SMB30MM</b></p> <p>Bracket: 30mm; Material: 12 Gauge Stainless Steel; Curved mounting slot for versatility/orientation ; Clearance for M6 (1/4 in.) hardware</p> |
|  | <p><b>SMB30SC</b></p> <p>Bracket: Compact 30 mm Swivel; Black reinforced thermoplastic polyester; Wide Range of Articulation ; Hardware included</p>                   |

|   |   |
|---|---|
|     | <p><b>SMB30A</b></p> <p>Bracket: Right Angle Mounting; Material: 12 Gauge Stainless Steel; Curved mounting slot for versatility/orientation ; Clearance for M6 (1/4 in.) hardware</p> |
|    | <p><b>SMB30S</b></p> <p>Bracket: Stainless Steel Mounting; Material: Black Polyester; 30 mm Swivel ; Hardware included</p>  |
|    | <p><b>SMBAMS30RA</b></p> <p>Bracket: 30mm Right Angle; Material: 12 Gauge cold rolled steel; Curved mounting slot for versatility/orientation</p>                                     |
|    | <p><b>SMB30FA</b></p> <p>SMB30FA MOUNTING BRACKET</p>   |
|    | <p><b>SMB30RAVK</b></p> <p>Bracket: V-Clamp Mount; 30 mm hole to 28 mm tube; Right-angle</p>  |
|    | <p><b>SMB30FVK</b></p> <p>SMB30FVK 30MM BRACKET ASSY</p>  |
|   | <p><b>SMBAMS30P</b></p> <p>Bracket: 30 mm flat bracket; Material: 12 Gauge Cold Rolled Steel; Curved mounting slot for versatility/orientation</p>                                    |
|  | <p><b>SMBQS30L</b></p> <p>Bracket: Stainless Steel Right-Angle; 14-ga Stainless Steel; Clearance for M4 ( no 8) Hardware; +/- 12 Degree Tilt Adjustment</p>                           |
|  | <p><b>SMB46L</b></p> <p>Bracket: L; Material: 14 Gauge 316 Stainless Steel</p>  |
|  | <p><b>SMB30SM</b></p> <p>Bracket: Swivel; Material: Black VALOX; Swivel ball is locked when bolts are tightened ; Hardware included</p>   |
|  | <p><b>SMB30C</b></p> <p>Bracket: Stainless Steel Mounting; Material: Black VALOX; 30mm split clamp ; Hardware included</p>  |
|  | <p><b>SMB30Q</b></p> <p>Bracket: 30 mm Angle Flanged Mounting; For use with Q40 Sensors</p>   |
|  | <p><b>SMB46U</b></p> <p>Bracket: U; Material: 14 Gauge 316 Stainless Steel</p>  |

|   |   |
|---|---|
|    | <p><b>SMB46S</b></p> <p>Bracket: S; Material: 14 Gauge 316 Stainless Steel</p>  |
|    | <p><b>SMB30FAM10</b></p> <p>SMB30FAM10 MOUNTING BRACKET, M10 X 50MM SHCS, M5 X 18MM SHCS</p>  |
|    | <p><b>SMBAMS30PL52</b></p> <p>SMBAMS30PL52 AUTOMOTIVE BRKT STRAIGHT LEGEND PLATE</p>  |
|    | <p><b>SMBAMS30RLS</b></p> <p>Bracket: Right Angle; 30 mm hole; Small Legend, Automotive Industry;</p>   |
|    | <p><b>SMBAMS30PL52R</b></p> <p>Bracket: Flat SMBAMS series with space; for 60 x 58 mm label; 30 mm hole for mounting sensors; Articulation slots for 90 plus degree rotation; 12-ga. (2.6 mm) Cold-rolled Steel</p> |
|    | <p><b>SMB30MM-62101</b></p> <p>SMB30MM-62101 MNTG BRKT QTY 2 30 MILLIMETER</p>  |
|    | <p><b>SMB30RAL52R</b></p> <p>Bracket: 30 mm Hole; 8.3 mm X 127 mm Slot; Zinc Plated Cold Rolled Steel</p>   |
|  | <p><b>SMBAMS30RAE</b></p> <p>Bracket: 30 mm Right Angle extended version; Material: 12 Gauge Cold Rolled Steel; Curved Mounting Slot for versatility/orientation</p>  |
|  | <p><b>SMB30FVKQ</b></p> <p>Bracket: 30 mm Bracket Assembly</p>  |

## ACCESSORIES

|   |   |
|---|---|
|  | <p><b>SMB30RAVKQ</b></p> <p>Bracket: 30 mm Bracket Assembly</p> |
|---|---|



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America

