

# **QS18VN6LAF250Q**

# QS18 SERIES ALL PURPOSE PHOTOELECTRIC SENSOR



WORLD-BEAM QS18 Laser Adjustable Field; Class 2 La

Rng: 20 mm-Cutoff pt (adj btwn 50-250 mm); Input:

Output: NPN

150mm Pigtail Pico Pigtail QD Connector

Part Number: 75736

# CERTIFICATIONS









#### **SPECIFICATIONS**

Sensing Mode (General)	Proximity
Sensing Mode (Detailed)	Background Suppression (Adjustable)
Housing Style	Rectangular
Primary Housing Material	Thermoplastic
Laser Classification	Class 2
Input/Output	Discrete
Max Sensing Range (mm)	250
Outputs	NPN
Power Supply/Supply Voltage	10-30 V dc
Connection	Pigtail QD
Quick Disconnect Type	M8 (Pico)

Sensing Beam	Laser
Operation	Light/Dark Operate
Max Op. Temp. (°C)	50
Min Op. Temp. (°C)	-10
Output response time (ms)	0.7
Special Feature: Intrinsically Safe	No
Special Feature: Remote Teach	No
Special Feature: Water Detection	No
IP Rating	IP67
Sensing Beam Wavelength	658
Delay at Power-up (ms)	200
Repeatability (μs)	13 0
Number of Pins	4
NEMA Rating	NEMA 6
NEMA Rating	NEMA 6
NEMA Rating  Max Op. Relative Humidity [%]	NEMA 6 95% @ 50°C
NEMA Rating  Max Op. Relative Humidity [%]  Lens Material	NEMA 6 95% @ 50°C Acrylic
NEMA Rating  Max Op. Relative Humidity [%]  Lens Material  Adjustments	NEMA 6  95% @ 50°C  Acrylic  Mechanical Screw
NEMA Rating  Max Op. Relative Humidity [%]  Lens Material  Adjustments  Barrel Diameter (mm)	NEMA 6  95% @ 50°C  Acrylic  Mechanical Screw
NEMA Rating  Max Op. Relative Humidity [%]  Lens Material  Adjustments  Barrel Diameter (mm)	NEMA 6  95% @ 50°C  Acrylic  Mechanical Screw  N/A
NEMA Rating  Max Op. Relative Humidity [%]  Lens Material  Adjustments  Barrel Diameter (mm)  Indicator  Opposed Mode Emitter/Receiver	NEMA 6  95% @ 50°C  Acrylic  Mechanical Screw  N/A  LEDs
NEMA Rating  Max Op. Relative Humidity [%]  Lens Material  Adjustments  Barrel Diameter (mm)  Indicator  Opposed Mode Emitter/Receiver  Feature: Timing (Hold/Delay)	NEMA 6  95% @ 50°C  Acrylic  Mechanical Screw  N/A  LEDs  N/A
NEMA Rating  Max Op. Relative Humidity [%]  Lens Material  Adjustments  Barrel Diameter (mm)  Indicator  Opposed Mode Emitter/Receiver  Feature: Timing (Hold/Delay)  Feature: Encapsulated	NEMA 6  95% @ 50°C  Acrylic  Mechanical Screw  N/A  LEDs  N/A  No
NEMA Rating  Max Op. Relative Humidity [%]  Lens Material  Adjustments  Barrel Diameter (mm)  Indicator  Opposed Mode Emitter/Receiver  Feature: Timing (Hold/Delay)  Feature: Encapsulated  Feature: Hazardous Area	NEMA 6  95% @ 50°C  Acrylic  Mechanical Screw  N/A  LEDs  N/A  No  No

# **RECOMMENDED PRODUCTS**

#### SINGLE ENDED CORDSETS



# ADAPTERS, BRACKETS, CLAMPS AND MOUNTING ACCESSORIES





Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America