



QS18VP6LAF W/30

► QS18 SERIES ALL PURPOSE PHOTOELECTRIC SENSOR



Range: 1 mm to cutoff pt; Adjust. cutoff pt 30-150 mm

Part Number: 73189

CERTIFICATIONS



SPECIFICATIONS

Sensing Mode (General)	Proximity
Sensing Mode (Detailed)	Background Suppression (Adjustable)
Housing Style	Rectangular
Primary Housing Material	Thermoplastic
Laser Classification	Class 1
Input/Output	Discrete
Max Sensing Range (mm)	150
Outputs	PNP
Power Supply/Supply Voltage	10-30 V dc
Connection	9 m Cable
Quick Disconnect Type	No QD

Sensing Beam	Laser
Operation	Light/Dark Operate
Max Op. Temp. (°C)	50
Min Op. Temp. (°C)	-10
Output response time (ms)	0.7
Special Feature: Intrinsically Safe	No
Special Feature: Remote Teach	No
Special Feature: Water Detection	No
IP Rating	IP67
Sensing Beam Wavelength	650
Delay at Power-up (ms)	200
Repeatability (µs)	130
Number of Pins	4
NEMA Rating	NEMA 6
Max Op. Relative Humidity [%]	95% @ 50°C
Lens Material	Acrylic
Adjustments	Mechanical Screw
Barrel Diameter (mm)	N/A
Indicator	LEDs
Opposed Mode Emitter/Receiver	N/A
Feature: Timing (Hold/Delay)	No
Feature: Encapsulated	No
Feature: Hazardous Area	No
Feature: Audible	No
Feature: Chemical Resistant	No
IO Link	No

RECOMMENDED PRODUCTS

ADAPTERS, BRACKETS, CLAMPS AND MOUNTING ACCESSORIES

	SMB18A Bracket: 18 mm Right Angle-mount; Material: 11 Gauge Stainless Steel; Curved mounting slot for versatility/orientation ; Clearance for M4 #8 hardware
	SMBQS18AF SMBQS18AF MOUNTING BRACKET ASSY
	SMBQS18YL SMBQS18YL MOUNTING BRACKET ASSY W/REPLACEABLE LENS COVER



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America