



## QS186EBQ

### ► QS18 SERIES ALL PURPOSE PHOTOELECTRIC SENSOR



WORLD-BEAM QS18 Series: Emitter (Flush Front)

Range: 3 m; Input: 10-30V dc

Output: Not applicable - No outputs

6 in Pigtail Pico-Style Pigtail QD Connector

Part Number: 61676

#### CERTIFICATIONS



#### SPECIFICATIONS

<b>Sensing Mode (General)</b>	Opposed
<b>Sensing Mode (Detailed)</b>	Emitter
<b>Housing Style</b>	Rectangular
<b>Primary Housing Material</b>	Thermoplastic
<b>Input/Output</b>	Discrete
<b>Max Sensing Range (mm)</b>	3000
<b>Power Supply/Supply Voltage</b>	10-30 V dc
<b>Connection</b>	Pigtail QD
<b>Quick Disconnect Type</b>	M8 (Pico)
<b>Sensing Beam</b>	Infrared LED
<b>Operation</b>	N/A



<b>Max Op. Temp. (°C)</b>	70
<b>Min Op. Temp. (°C)</b>	-20
<b>Output response time (ms)</b>	N/A
<b>Special Feature: Intrinsically Safe</b>	No
<b>Special Feature: Remote Teach</b>	No
<b>Special Feature: Water Detection</b>	No
<b>IP Rating</b>	IP67
<b>Delay at Power-up (ms)</b>	100
<b>Repeatability (µs)</b>	100
<b>Number of Pins</b>	4
<b>NEMA Rating</b>	NEMA 6
<b>Max Op. Relative Humidity [%]</b>	95% @ 50°C
<b>Lens Material</b>	Acrylic
<b>Adjustments</b>	N/A
<b>Barrel Diameter (mm)</b>	N/A
<b>Indicator</b>	LEDs
<b>Opposed Mode Emitter/Receiver</b>	Emitter
<b>Feature: Timing (Hold/Delay)</b>	No
<b>Feature: Encapsulated</b>	No
<b>Feature: Hazardous Area</b>	No
<b>Feature: Audible</b>	No
<b>Feature: Chemical Resistant</b>	No
<b>IO Link</b>	No

## RECOMMENDED PRODUCTS

## SINGLE ENDED CORDSETS

	<b>PKG4-2</b>
	Pico-style Quick Disconnect Cable; 4 Pin Straight Connector; 2 m (6.5 ft) in Length; POM snap-lock coupling
	<b>PKW4Z-2</b>
	Pico-style Quick Disconnect Cable; 4 Pin Right Angle Connector; 2 m (6.5 ft) in Length; POM snap-lock coupling

## ADAPTERS, BRACKETS, CLAMPS AND MOUNTING ACCESSORIES

	<b>SMB18A</b>
	Bracket: 18 mm Right Angle-mount; Material: 11 Gauge Stainless Steel; Curved mounting slot for versatility/orientation ; Clearance for M4 #8 hardware
	<b>SMB312S</b>
	Bracket: Side Mounting; Material: Stainless Steel 2-axis

## APERTURES

	<b>APQS18-020</b>
	APQS18-020 APERTURE QS18 SERIES - QTY 6
	<b>APQS18-020H</b>
	APQS18-020H APERTURE QS18 SERIES - QTY 6
	<b>APQS18-020V</b>
	APQS18-020V APERTURE QS18 SERIES - QTY 6
	<b>APQS18-040</b>
	APQS18-040 APERTURE QS18 SERIES QTY 6
	<b>APQS18-040H</b>
	APQS18-040H APERTURE QS18 SERIES - QTY 6
	<b>APQS18-040V</b>
	APQS18-040V APERTURE QS18 SERIES - QTY 6
	<b>APQS18-100</b>
	APQS18-100 APERTURE QS18 SERIES QTY 6
	<b>APQS18-100H</b>
	APQS18-100H APERTURE QS18 SERIES QTY 6

	<b>APQS18-100V</b>
	APQS18-100V APERTURE QS18 SERIES QTY 6
	<b>APQS18-DVHX2</b>
	APQS18-DVHX2 APERTURE QS18 SERIES QTY 18



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America