



QS18AP6AFF200QPMA20

► QS18 SERIES ALL PURPOSE PHOTOELECTRIC SENSOR



WORLD-BEAM: Adjustable Field Foreground Suppression

Cutoff Adjustment Range: 30-200mm; Input:10-30V dc

Output; PNP

150mm PUR Euro, pin 2 open, L.O.

Part Number: 11475

CERTIFICATIONS



SPECIFICATIONS

Sensing Mode (General)	Proximity
Sensing Mode (Detailed)	Foreground Suppression (Adjustable)
Housing Style	Rectangular
Primary Housing Material	Thermoplastic
Input/Output	Discrete
Max Sensing Range (mm)	200
Outputs	PNP
Power Supply/Supply Voltage	10-30 V dc
Connection	Pigtail PUR QD
Quick Disconnect Type	M12 (Euro)
Sensing Beam	Visible Red LED

Operation	Light Operate
Max Op. Temp. (°C)	55
Min Op. Temp. (°C)	-20
Output response time (ms)	2.5
Special Feature: Intrinsically Safe	No
Special Feature: Remote Teach	No
Special Feature: Water Detection	No
IP Rating	IP67
Delay at Power-up (ms)	200
Repeatability (µs)	250
Number of Pins	4
NEMA Rating	NEMA 6
Max Op. Relative Humidity [%]	95% @ 50°C
Lens Material	Acrylic
Adjustments	Mechanical Screw
Barrel Diameter (mm)	N/A
Indicator	LEDs
Opposed Mode Emitter/Receiver	N/A
Feature: Timing (Hold/Delay)	No
Feature: Encapsulated	No
Feature: Hazardous Area	No
Feature: Audible	No
Feature: Chemical Resistant	No
IO Link	No

RECOMMENDED PRODUCTS

ADAPTERS, BRACKETS, CLAMPS AND MOUNTING ACCESSORIES

	SMB312S Bracket: Side Mounting; Material: Stainless Steel 2-axis
	SMBQS18Y SMBQS18Y MOUNTING BRACKET ASSY
	SMBQS18A SMBQS18A MOUNTING BRACKET ASSY
	SMB30SUS Bracket: Side Mounting Swivel; Extended range of motion; Black thermoplastic polyester; Allows Maximum Articulation
	SMB46L Bracket: L; Material: 14 Gauge 316 Stainless Steel
	SMB46U Bracket: U; Material: 14 Gauge 316 Stainless Steel
	SMBQS18RA SMBQS18RA MOUNTING BRACKET
	SMB4050YL SMB4050YL MOUNTING BRACKET ASSY W/REPLACEABLE LENS COVER
	SMB46S Bracket: S; Material: 14 Gauge 316 Stainless Steel
	SMBQS18DIN SMBQS18DIN MOUNTING BRACKET ASSY



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America

