



QS18EN6LPQ7

► QS18 SERIES ALL PURPOSE PHOTOELECTRIC SENSOR



WORLD-BEAM QS18 Expert Series: Polar Retro
 Range: 3.5 m; Input: 10 to 30 V dc
 Output: Complementary Solid State NPN
 Integral Pico-Style Quick-Disconnect Connector
 Part Number: 71998

CERTIFICATIONS



SPECIFICATIONS

Sensing Mode (General)	Retroreflective
Sensing Mode (Detailed)	Polarized
Housing Style	Rectangular w/M18 Mount
Primary Housing Material	Thermoplastic
Input/Output	Discrete
Max Sensing Range (mm)	3500
Outputs	NPN
Power Supply/Supply Voltage	10-30 V dc
Connection	Integral QD
Quick Disconnect Type	M8 (Pico)
Sensing Beam	Visible Red LED











Operation	Light/Dark Operate
Max Op. Temp. (°C)	70
Min Op. Temp. (°C)	-20
Output response time (ms)	0.6
Special Feature: Intrinsically Safe	No
Special Feature: Remote Teach	Yes
Special Feature: Water Detection	No
IP Rating	IP67
Delay at Power-up (ms)	100
Repeatability (µs)	75
Number of Pins	4
NEMA Rating	NEMA 6
Max Op. Relative Humidity [%]	95% @ 50°C
Lens Material	PMMA
Adjustments	Teach Button
Barrel Diameter (mm)	18
Indicator	LEDs
Opposed Mode Emitter/Receiver	N/A
Feature: Timing (Hold/Delay)	Yes
Feature: Encapsulated	No
Feature: Hazardous Area	No
Feature: Audible	No
Feature: Chemical Resistant	No
IO Link	No

RECOMMENDED PRODUCTS











SINGLE ENDED CORDSETS

	PKG4-2
	Pico-style Quick Disconnect Cable; 4 Pin Straight Connector; 2 m (6.5 ft) in Length; POM snap-lock coupling
	PKW4Z-2
	Pico-style Quick Disconnect Cable; 4 Pin Right Angle Connector; 2 m (6.5 ft) in Length; POM snap-lock coupling

ADAPTERS, BRACKETS, CLAMPS AND MOUNTING ACCESSORIES



	SMB18A
	Bracket: 18 mm Right Angle-mount; Material: 11 Gauge Stainless Steel; Curved mounting slot for versatility/orientation ; Clearance for M4 #8 hardware
	SMB18SF
	Bracket: 18 mm Swivel; Material: Black VALOX; Mounting Flange; Swivel Locking Hardware Included
	SMB312S
	Bracket: Side Mounting; Material: Stainless Steel 2-axis
	SMB18FA
	Bracket: Kit for 12 mm (1/2 in.) Rod Bracket Systems for; most 18 mm barrel mount sensors; lights; and brackets; Includes 3/8-16 X 2 in. Socket Head Cap Screw (SHCS)
	SMB312PD
	Bracket: 18 mm Barrel Mounting; Material: Stainless Steel
	SMB18S
	Bracket: 18 mm Swivel; Material: Black VALOX; 18 mm swivel; Hardware included
	SMBQS18Y
	SMBQS18Y MOUNTING BRACKET ASSY
	SMB18UR
	Bracket: 2 part universal rotating stainless steel; Allows full horizontal movement; Allows full vertical movement
	SMBQS18A
	SMBQS18A MOUNTING BRACKET ASSY
	SMB3018SC
	Bracket: 18 mm swivel barrel or side mounting; Black reinforced thermoplastic polyester; Hardware included

	<p>SMB30SUS</p> <p>Bracket: Side Mounting Swivel; Extended range of motion; Black thermoplastic polyester; Allows Maximum Articulation</p>
	<p>SMBAMS18RA</p> <p>Bracket: Right-angle SMBAMS series with; 18 mm hole for mounting sensors; Articulation slots for 90 plus degree rotation; 12-ga. (2.6 mm) Cold-rolled Steel</p>
	<p>SMB46L</p> <p>Bracket: L; Material: 14 Gauge 316 Stainless Steel</p>
	<p>SMBAMS18P</p> <p>Bracket: Flat SMBAMS series with 18 mm ; hole for mounting sensors; Articulation slots for 90 plus degree rotation; 12-ga. (2.6 mm) Cold-rolled Steel</p>
	<p>SMB18Q</p> <p>Bracket: 18 mm Angled Flanged-Mount; Material: 12 Guage Stainless Steel; Barrel-Mount</p>
	<p>SMB30SK</p> <p>Bracket: Flat mount swivel with extended range; Allows full articulation; Black thermoplastic polyester & 316 stainless stee; Hardware included</p>
	<p>SMB46A</p> <p>Bracket: Adjustable; Stainless Steel; Includes: 2 mm shortarm hex keys</p>
	<p>SMB18AFA</p> <p>Bracket: Covered Mounting Bracket</p>
	<p>SMB18C</p> <p>Bracket: Stainless Steel Mounting; Material: Black VALOX; 18mm split clamp ; Hardware included</p>
	<p>SMB18FAM10</p> <p>Bracket: Kit for 10 mm (3/8 in) Rod Bracket Systems for; most 18 mm barrel mount sensors; lights; and brackets; Includes M10-1.5 X 50 mm Socket Head Cap Screw (SHCS)</p>
	<p>SMB46U</p> <p>Bracket: U; Material: 14 Gauge 316 Stainless Steel</p>
	<p>SMBQS18RA</p> <p>SMBQS18RA MOUNTING BRACKET</p>
	<p>SMB4050YL</p> <p>SMB4050YL MOUNTING BRACKET ASSY W/REPLACEABLE LENS COVER</p>

	<p>SMB46S</p> <p>Bracket: S; Material: 14 Gauge 316 Stainless Steel</p>
	<p>SMB18FM</p> <p>SMB18FM FLANGE MOUNT 18MM BRACKET KIT</p>
	<p>SMB18WT</p> <p>Bracket: 2 part universal rotating stainless steel; Allows full horizontal/vertical movement, modified for DS18 AC models</p>
	<p>SMB1812SF</p> <p>Bracket: Swivel; Compact 12mm; Black reinforced thermoplastic polyester; Hardware included</p>
	<p>SMB18FAB</p> <p>SMB18FAB MOUNTING BRACKET; 121704</p>
	<p>SMB18SM</p> <p>Bracket: Mounts by its base; Material: Black VALOX; Flexible and Convienient ; Hardware included</p>
	<p>SMB18RAVK</p> <p>SMB18RAVK 18MM BRACKET ASSY</p>
	<p>SMBC18</p> <p>Bracket: 28 mm Creform Mounting ; Material: Plastic; For 18 mm Lights and Sensors</p>
	<p>SMB18AFAM10</p> <p>Bracket: Covered Mounting Bracket with 10 mm Screw</p>
	<p>SMB18ATFA</p> <p>SMB18ATFA COVERED MOUNTING BRACKET, 115MM LONG 4 MOUNTING HOLES</p>
	<p>SMBQS18DIN</p> <p>SMBQS18DIN MOUNTING BRACKET ASSY</p>
	<p>SMBQS18WRS</p> <p>SMBQS18WRS</p>
	<p>SMB18UR-2</p> <p>SMB18UR-2 MOUNTING BRKT. ASSY</p>
	<p>SMB18ATFAM10</p> <p>SMB18ATFAM10 COVERED MOUNTING BRACKET,115MM LONG 4 MOUNTING HOLES, W/10MM SCREW</p>

	SMB18AZ
	SMB18AZ MOUNTING BRACKET ASSY METAL BRACKET CHINA ONLY
	SMB18FVK
	SMB18FVK 18MM BRACKET ASSY
	SMB18URZ
	SMB18URZ MOUNTING BRACKET ASSY CHINA ONLY

RETROREFLECTIVE TARGET

	BRT-2X2
	Retroreflective Target: Rectangular -51x51mm; Reflectivity Factor: 1.0; Max. Temp.= 50 degrees C; Plastic - two screw holes for mounting
	BRT-84
	BRT-84



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America