



QS18ANWRC1

► QS18 SERIES ALL PURPOSE PHOTOELECTRIC SENSOR



WORLD-BEAM QS18 Universal Voltage; Opposed Infrared

Range:20 m; Input: 20 to 270V ac/dc

Output:LO; N-MOSFET (Sinking)

2m 600 Volt Cable

Part Number: 81336

CERTIFICATIONS
















SPECIFICATIONS














| | |
|------------------------------------|-------------------------|
| Sensing Mode (General) | Opposed |
| Sensing Mode (Detailed) | Receiver |
| Housing Style | Rectangular w/M18 Mount |
| Primary Housing Material | Thermoplastic |
| Input/Output | Discrete |
| Max Sensing Range (mm) | 20000 |
| Outputs | N-MOSFET (Sinking) |
| Power Supply/Supply Voltage | 20-270 V ac/dc |
| Connection | 2 m Cable |
| Quick Disconnect Type | No QD |
| Operation | Light Operate |










| | |
|--|----------------------------|
| Max Op. Temp. (°C) | 70 if < 140V, 55 if > 140V |
| Min Op. Temp. (°C) | -25 |
| Output response time (ms) | 16.6 |
| Special Feature: Intrinsically Safe | No |
| Special Feature: Remote Teach | No |
| Special Feature: Water Detection | No |
| IP Rating | IP67 |
| Delay at Power-up (ms) | 100ms dc, 300ms ac |
| Repeatability (µs) | 1500 |
| Number of Pins | 3 |
| NEMA Rating | NEMA 6 |
| Max Op. Relative Humidity [%] | 95% @ 55°C |
| Lens Material | PMMA |
| Adjustments | N/A |
| Barrel Diameter (mm) | 18 |
| Indicator | LEDs |
| Opposed Mode Emitter/Receiver | Receiver |
| Feature: Timing (Hold/Delay) | No |
| Feature: Encapsulated | No |
| Feature: Hazardous Area | No |
| Feature: Audible | No |
| Feature: Chemical Resistant | No |
| IO Link | No |

RECOMMENDED PRODUCTS

ADAPTERS, BRACKETS, CLAMPS AND MOUNTING ACCESSORIES

| | |
|---|--|
|  | <p>SMB18A</p> <p>Bracket: 18 mm Right Angle-mount; Material: 11 Gauge Stainless Steel; Curved mounting slot for versatility/orientation ; Clearance for M4 #8 hardware</p> |
|  | <p>SMB18SF</p> <p>Bracket: 18 mm Swivel; Material: Black VALOX; Mounting Flange; Swivel Locking Hardware Included</p> |
|  | <p>SMB312S</p> <p>Bracket: Side Mounting; Material: Stainless Steel 2-axis</p> |
|  | <p>SMB18FA</p> <p>Bracket: Kit for 12 mm (1/2 in.) Rod Bracket Systems for; most 18 mm barrel mount sensors; lights; and brackets; Includes 3/8-16 X 2 in. Socket Head Cap Screw (SHCS)</p> |
|  | <p>SMB312PD</p> <p>Bracket: 18 mm Barrel Mounting; Material: Stainless Steel</p> |
|  | <p>SMB18S</p> <p>Bracket: 18 mm Swivel; Material: Black VALOX; 18 mm swivel; Hardware included</p> |
|  | <p>SMB18UR</p> <p>Bracket: 2 part universal rotating stainless steel; Allows full horizontal movement; Allows full vertical movement</p> |
|  | <p>SMB3018SC</p> <p>Bracket: 18 mm swivel barrel or side mounting; Black reinforced thermoplastic polyester; Hardware included</p> |
|  | <p>SMB30SUS</p> <p>Bracket: Side Mounting Swivel; Extended range of motion; Black thermoplastic polyester; Allows Maximum Articulation</p> |
|  | <p>SMBAMS18RA</p> <p>Bracket: Right-angle SMBAMS series with; 18 mm hole for mounting sensors; Articulation slots for 90 plus degree rotation; 12-ga. (2.6 mm) Cold-rolled Steel</p> |
|  | <p>SMB46L</p> <p>Bracket: L; Material: 14 Gauge 316 Stainless Steel</p> |
|  | <p>SMBAMS18P</p> <p>Bracket: Flat SMBAMS series with 18 mm ; hole for mounting sensors; Articulation slots for 90 plus degree rotation; 12-ga. (2.6 mm) Cold-rolled Steel</p> |
|  | <p>SMB18Q</p> <p>Bracket: 18 mm Angled Flanged-Mount; Material: 12 Gauge Stainless Steel; Barrel-Mount</p> |

| | |
|---|---|
|  | <p>SMB30SK</p> <p>Bracket: Flat mount swivel with extended range; Allows full articulation; Black thermoplastic polyester & 316 stainless steel; Hardware included</p> |
|  | <p>SMB46A</p> <p>Bracket: Adjustable; Stainless Steel; Includes: 2 mm shortarm hex keys</p> |
|  | <p>SMB18AFA</p> <p>Bracket: Covered Mounting Bracket</p> |
|  | <p>SMBQS18VP6LPQ</p> <p>BRACKET SMBQS18VP6LPQ; 123459</p> |
|  | <p>SMB18C</p> <p>Bracket: Stainless Steel Mounting; Material: Black VALOX; 18mm split clamp ; Hardware included</p> |
|  | <p>SMB18FAM10</p> <p>Bracket: Kit for 10 mm (3/8 in) Rod Bracket Systems for; most 18 mm barrel mount sensors; lights; and brackets; Includes M10-1.5 X 50 mm Socket Head Cap Screw (SHCS)</p> |
|  | <p>SMB46U</p> <p>Bracket: U; Material: 14 Gauge 316 Stainless Steel</p> |
|  | <p>SMB46S</p> <p>Bracket: S; Material: 14 Gauge 316 Stainless Steel</p> |
|  | <p>SMB18FM</p> <p>SMB18FM FLANGE MOUNT 18MM BRACKET KIT</p> |
|  | <p>SMB18WT</p> <p>Bracket: 2 part universal rotating stainless steel; Allows full horizontal/vertical movement, modified for DS18 AC models</p> |
|  | <p>SMB1812SF</p> <p>Bracket: Swivel; Compact 12mm; Black reinforced thermoplastic polyester; Hardware included</p> |
|  | <p>SMB18FAB</p> <p>SMB18FAB MOUNTING BRACKET; 121704</p> |
|  | <p>SMB18SM</p> <p>Bracket: Mounts by its base; Material: Black VALOX; Flexible and Convenient ; Hardware included</p> |

| | |
|---|---|
|  | <p>SMB18RAVK</p> <p>SMB18RAVK 18MM BRACKET ASSY</p> |
|  | <p>SMBC18</p> <p>Bracket: 28 mm Creform Mounting ; Material: Plastic; For 18 mm Lights and Sensors</p> |
|  | <p>SMB18AFAM10</p> <p>Bracket: Covered Mounting Bracket with 10 mm Screw</p> |
|  | <p>SMB18ATFA</p> <p>SMB18ATFA COVERED MOUNTING BRACKET, 115MM LONG 4 MOUNTING HOLES</p> |
|  | <p>SMBQS18DIN</p> <p>SMBQS18DIN MOUNTING BRACKET ASSY</p> |
|  | <p>SMBQS18WRS</p> <p>SMBQS18WRS</p> |
|  | <p>SMB18UR-2</p> <p>SMB18UR-2 MOUNTING BRKT. ASSY</p> |
|  | <p>SMB18ATFAM10</p> <p>SMB18ATFAM10 COVERED MOUNTING BRACKET,115MM LONG 4 MOUNTING HOLES, W/10MM SCREW</p> |
|  | <p>SMB18FVK</p> <p>SMB18FVK 18MM BRACKET ASSY</p> |

APERTURES

| | |
|---|---|
|  | <p>APQS18-020</p> <p>APQS18-020 APERTURE QS18 SERIES - QTY 6</p> |
|  | <p>APQS18-020H</p> <p>APQS18-020H APERTURE QS18 SERIES - QTY 6</p> |
|  | <p>APQS18-020V</p> <p>APQS18-020V APERTURE QS18 SERIES - QTY 6</p> |
|  | <p>APQS18-040</p> <p>APQS18-040 APERTURE QS18 SERIES QTY 6</p> |

| | |
|---|---|
|  | APQS18-040H APQS18-040H APERTURE QS18 SERIES - QTY 6 |
|  | APQS18-040V APQS18-040V APERTURE QS18 SERIES - QTY 6 |
|  | APQS18-100 APQS18-100 APERTURE QS18 SERIES QTY 6 |
|  | APQS18-100H APQS18-100H APERTURE QS18 SERIES QTY 6 |
|  | APQS18-100V APQS18-100V APERTURE QS18 SERIES QTY 6 |
|  | APQS18-DVHX2 APQS18-DVHX2 APERTURE QS18 SERIES QTY 18 |



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America